

# Data Sheet

## Fujitsu PRIMERGY CX2570 M2 PRIMERGY Cloud Servers

HPC optimized server node for PRIMERGY CX400 M1 multi-node server system

---

### PRIMERGY CX2570 M2

The PRIMERGY CX2570 M2 is a compact server node enabling high computing density with two independent servers in 2U. It is ideal for ambitious high performance computing, analytics and visualization solutions. Two server nodes can be embedded in the PRIMERGY CX400 M1 enclosure, only using 2U height in conventional standard datacenter racks. The PRIMERGY CX2570 M2 combines high-end computational and graphics performance with high energy efficiency. Each half-wide server node with Intel® Xeon® processor E5-2600 v4 product family CPUs and 16 DDR4 memory DIMMs, features up to two optional NVIDIA® GPGPU or Intel® Xeon Phi™ co-processor cards, enabling a performance boost in supported applications.



# Features & Benefits

Main Features	Benefits
<p><b>Compact form factor</b></p> <ul style="list-style-type: none"> <li>Two PRIMERGY CX2570 M2 server nodes, each with two processors, 16 DDR4 memory DIMMs, support for two NVIDIA® or Intel® GPGPU or co-processor cards, and up to six local storage drives, are smartly packaged into a condensed 2U rack enclosure.</li> </ul> <p><b>Latest technology</b></p> <ul style="list-style-type: none"> <li>Up to two Intel® Xeon® processor E5-2600 v4 product family with up to 22 cores and 55 MB cache, advanced Turbo Boost 2.0 technology, Hyper Threading, two accelerated QPI links and internal Memory Management Unit.</li> <li>16 DIMMs per server node with up to 1,024 GB DDR4 memory and up to 2,400 MHz DRAM bandwidth.</li> <li>Cool-safe® Advanced Thermal Design enables operation in a higher ambient temperature.</li> </ul> <p><b>High-end GPGPU and co-processors for scale-out HPC computing</b></p> <ul style="list-style-type: none"> <li>2 optional GPGPU or co-processor compute cards per CX2570 M2 server node, selected from the market leading NVIDIA® Tesla™ or the Intel® Xeon Phi™ product family.</li> </ul> <p><b>Shared infrastructure &amp; easy serviceability</b></p> <ul style="list-style-type: none"> <li>Server nodes share central cooling fans and hot plug power supplies in the 2U PRIMERGY CX400 M1 chassis.</li> <li>Hot-plug for server nodes, power supplies and disk drives enable enhanced availability and easy serviceability.</li> </ul>	<ul style="list-style-type: none"> <li>50% less rack space used as compared to equivalent standard rack servers. Higher server density results in more performance per rack unit.</li> <li>Boost your general computing performance by up to 38% compared to the previous generation.</li> <li>The new DDR4 memory technology provides higher performance with lower power requirements.</li> <li>Each additional degree in the data center means approximately 5-6 percent less energy costs for air-conditioning</li> <li>High performance GPGPUs or co-processors from NVIDIA or Intel make them ideal for seismic processing, biochemistry simulations, weather and climate modeling, signal processing, computational finance, CAE, CFD, data analytics and other high performance computing areas.</li> <li>Decreased energy consumption, lower investment, yet still redundant operation. Lower energy budgets for a comparable performance as with standard rack servers.</li> <li>Each single server can be serviced without affecting the other nodes in the chassis. Redundancy for shared components provides uniform higher availability.</li> </ul>

# Technical details

## PRIMERGY CX2570 M2

Housing types	Air-cooled node
Product Type	Dual Socket 2U Server Node
<b>Mainboard</b>	
Mainboard type	D 3343
Chipset	Intel® C610
Processor quantity and type	2 x Intel® Xeon® processor E5-2600 v4 product family
Graphics add on cards (optional)	Remote Graphics: NVIDIA® Tesla® M60, 4096 cores, PCIe 3.0 x16
Graphics add on cards	Remote Graphics: NVIDIA® Tesla® M60, 4,096 cores, PCIe 3.0 x16
	GPU computing card: NVIDIA® Tesla® P100, 3584 cores, PCIe 3.0 x16
Intel® Xeon® processor E5-2699v4 (22C/44T, 2.20 GHz, up to 2.8 GHz, 9.6 GT/s)	
Intel® Xeon® processor E5-2699Av4 (22C/44T, 2.40 GHz, up to 3.0 GHz, 9.6 GT/s)	
Intel® Xeon® processor E5-2698v4 (20C/40T, 2.20 GHz, up to 2.7 GHz, 9.6 GT/s)	
Intel® Xeon® processor E5-2697v4 (18C/36T, 2.30 GHz, up to 2.8 GHz, 9.6 GT/s)	
Intel® Xeon® processor E5-2697Av4 (16C/32T, 2.60 GHz, up to 3.1 GHz, 9.6 GT/s)	
Intel® Xeon® processor E5-2695v4 (18C/36T, 2.10 GHz, up to 2.6 GHz, 9.6 GT/s)	
Intel® Xeon® processor E5-2690v4 (14C/28T, 2.60 GHz, up to 3.2 GHz, 9.6 GT/s)	
Intel® Xeon® processor E5-2683v4 (16C/32T, 2.10 GHz, up to 2.6 GHz, 9.6 GT/s)	
Intel® Xeon® processor E5-2680v4 (14C/28T, 2.40 GHz, up to 2.9 GHz, 9.6 GT/s)	
Intel® Xeon® processor E5-2667v4 (8C/16T, 3.20 GHz, up to 3.5 GHz, 9.6 GT/s)	
Intel® Xeon® processor E5-2660v4 (14C/28T, 2.00 GHz, up to 2.4 GHz, 9.6 GT/s)	
Intel® Xeon® processor E5-2650v4 (12C/24T, 2.20 GHz, up to 2.5 GHz, 9.6 GT/s)	
Intel® Xeon® processor E5-2650Lv4 (14C/28T, 1.70 GHz, up to 2.0 GHz, 9.6 GT/s)	
Intel® Xeon® processor E5-2643v4 (6C/12T, 3.40 GHz, up to 3.6 GHz, 9.6 GT/s)	
Intel® Xeon® processor E5-2640v4 (10C/20T, 2.40 GHz, up to 2.6 GHz, 8.0 GT/s)	
Intel® Xeon® processor E5-2637v4 (4C/8T, 3.50 GHz, up to 3.6 GHz, 9.6 GT/s)	
Intel® Xeon® processor E5-2630v4 (10C/20T, 2.20 GHz, up to 2.4 GHz, 8.0 GT/s)	
Intel® Xeon® processor E5-2630Lv4 (10C/20T, 1.80 GHz, up to 2.0 GHz, 8.0 GT/s)	
Intel® Xeon® processor E5-2623v4 (4C/8T, 2.60 GHz, up to 2.9 GHz, 8.0 GT/s)	
Intel® Xeon® processor E5-2620v4 (8C/16T, 2.10 GHz, up to 2.3 GHz, 8.0 GT/s)	
Intel® Xeon® processor E5-2609v4 (8C/8T, 1.70 GHz, 6.4 GT/s)	
Intel® Xeon® processor E5-2603v4 (6C/6T, 1.70 GHz, 6.4 GT/s)	
Memory slots	16 / 4 channels per CPU with 8 DIMMs per CPU = 16 DIMMs in total
Memory capacity (min. - max.)	16 GB - 1024 GB
Memory protection	Advanced ECC SDDC
Memory notes	Supports R-DIMM, LR-DIMM
8 GB (1 8 GB) DDR4, registered, ECC, 2,400 MT/s, PC4-2400T-R, DIMM, 1Rx4	
8 GB (1 8 GB) DDR4, registered, ECC, 2,400 MT/s, PC4-2400T-R, DIMM, 2Rx8	
16 GB (1 16 GB) DDR4, registered, ECC, 2,400 MT/s, PC4-2400T-R, DIMM, 1Rx4	
16 GB (1 16 GB) DDR4, registered, ECC, 2,400 MT/s, PC4-2400T-R, DIMM, 2Rx4	
16 GB (1 16 GB) DDR4, registered, ECC, 2,400 MT/s, PC4-2400T-R, DIMM, 2Rx8	
32 GB (1 32 GB) DDR4, registered, ECC, 2,400 MT/s, PC4-2400T-R, DIMM, 2Rx4	
64 GB (1 64 GB) DDR4, registered, ECC, 2,400 MT/s, PC4-2400T-L, LRDIMM, 4Rx4	
64 GB (1 64 GB) DDR4 3DS, registered, ECC, 2,400 MT/s, PC4-2400T-R, DIMM, 4Rx4	
Notes	2x in CX400 M1
<b>Interfaces</b>	
USB 3.x ports	2 x USB 3.0 (rear)

**Interfaces**

Graphics (15-pin)	1 x VGA (1x rear)
LAN / Ethernet (RJ-45)	3 / 2x Gbit/s Ethernet + 1x service LAN Onboard
Management LAN (RJ45)	Management LAN traffic can be switched to shared onboard Gbit LAN port

**Onboard or integrated Controller**

RAID controller	RAID 0/1 for internal drives
SATA Controller	Intel® C610, for up to 6x 2.5inch SATA HDD or SSD Raid 0/1
LAN Controller	Intel® Ethernet Controller I350 2 x 10/100/1000 Mbit/s Ethernet (TCP/IP acceleration)
Remote management controller	Integrated Remote Management Controller (iRMC S4, 256 MB attached memory incl. graphics controller) IPMI 2.0 compatible

**Slots**

PCI-Express 3.0 x16	4 x (2x for low profile and 2x special riser w/ PCIe Gen3 for GPGPU only)
---------------------	---

**Drive bays**

Storage drive bays	up to 6x 2.5-inch (in the PRIMERGY CX400 M1 chassis)
Storage drive bay configuration	depending on hardware configuration

**General system information**

Number of fans	0
Fan configuration	Centralized non-hot plug fans part of CX400 Chassis

**Operating panel**

Operating buttons	On/off switch ID button
Status LEDs	Power (green) System status (orange) LAN speed (green / yellow) LAN connection (green) Identification (blue)

**BIOS**

BIOS features	UEFI compliant Legacy BIOS compatibility customer configuration option Secure boot support ROM based setup utility GPT support for boot drives larger than 2.2 TB IPMI support Recovery BIOS BIOS settings save and restore Local BIOS update from USB device Online update tools for main Linux versions Local and remote update via ServerView Update Manager IPv4/IPv6 remote PXE & iSCSI boot support
---------------	--

## Operating Systems and Virtualization Software

Certified or supported operating systems  
and virtualization software

Windows Server 2016 Datacenter  
Windows Server 2016 Standard  
Windows Server 2016 Essentials  
Windows Storage Server 2016 Standard  
Windows Server Datacenter, version 1709  
Hyper-V Server 2012 R2  
Windows Server 2012 R2 Datacenter  
Windows Server 2012 R2 Standard  
Windows Server 2012 R2 Essentials  
Windows Storage Server 2012 R2 Standard  
VMware vSphere™ 6.7  
VMware vSphere™ 6.5  
VMware vSphere™ 6.0  
VMware vSphere™ 5.5  
SUSE® Linux Enterprise Server 12  
SUSE® Linux Enterprise Server 11  
Red Hat® Enterprise Linux 7  
Red Hat® Enterprise Linux 6  
Citrix® XenServer®

### Operating system notes

Operating system release link <http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473>

### Dimensions

Dimensions (W x D x H) 175.5 x 520 x 84 mm  
Weight 8 kg  
Node size 2 U half wide (W175.5 x D520 x H84 mm)

### Environment

Operating ambient temperature 5 - 40 °C (41 - 104 °F)  
Operating relative humidity 10 - 85 % (non condensing)  
Temperature and humidity notes Cool-safe® Advanced Thermal Design (above 35 °C or below 10 °C) depending on configuration. For detailed information see relevant system configurator.  
Maximum altitude 3000 m  
Operating environment FTS 04230 – Guideline for Data Center (installation specification)  
Operating environment link <http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe>

### Compliance

Global CB  
RoHS (Substance limitations in accordance with global RoHS regulations)  
WEEE (Waste electrical and electronic equipment)  
IEC 60950  
Europe CE Class A \*  
EN 60950 - 1  
EN 50371  
EN 55022  
EN 61000-3-3  
EN 55024  
USA/Canada UL/CSA  
ICES-003 / NMB-003 Class A  
Japan VCCI Class A  
Taiwan CNS 13436  
CNS 13438 class A  
Compliance link <https://sp.ts.fujitsu.com/sites/certificates>

## Compliance

### Compliance notes

There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request.

\* Warning:  
This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.

# Components

Hard disk drives	HDD SATA, 6 Gb/s, 500 GB, 7,200 rpm, hot-plug, 2.5-inch, business critical
	HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, 512e, hot-plug, 2.5-inch, business critical
Hard disk drives	HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, hot-plug, 2.5-inch, business critical
	HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, 512e, hot-plug, 2.5-inch, business critical
Hard disk drives	HDD SAS, 12 Gb/s, 900 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 900 GB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 600 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise, SED
	HDD SAS, 12 Gb/s, 450 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 300 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 300 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise, SED
	HDD SAS, 12 Gb/s, 300 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 2 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical
	HDD SAS, 12 Gb/s, 1.8 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise, SED
	HDD SAS, 12 Gb/s, 1.8 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise, SED
	HDD SAS, 12 Gb/s, 1 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical
	SSD SATA, 6 Gb/s, 960 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPDP (Drive Writes Per Day for 5 years)
	SSD SATA, 6 Gb/s, 960 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPDP (drive writes per day for 5 years)
	SSD SATA, 6 Gb/s, 800 GB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPDP (drive writes per day for 5 years)
	SSD SATA, 6 Gb/s, 800 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPDP (Drive Writes Per Day for 5 years)
	SSD SATA, 6 Gb/s, 480 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3.6 DWPDP (Drive Writes Per Day for 5 years)
	SSD SATA, 6 Gb/s, 480 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPDP (drive writes per day for 5 years)
	SSD SATA, 6 Gb/s, 400 GB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPDP (drive writes per day for 5 years)
	SSD SATA, 6 Gb/s, 240 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPDP (Drive Writes Per Day for 5 years)
	SSD SATA, 6 Gb/s, 240 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3.6 DWPDP (Drive Writes Per Day for 5 years)
	SSD SATA, 6 Gb/s, 240 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPDP (drive writes per day for 5 years)
	SSD SATA, 6 Gb/s, 200 GB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPDP (drive writes per day for 5 years)
	SSD SATA, 6 Gb/s, 120 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPDP (drive writes per day for 5 years)
	SSD SATA, 6 Gb/s, 1.92 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPDP (drive writes per day for 5 years)
	SSD SATA, 6 Gb/s, 1.6 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPDP (Drive Writes Per Day for 5 years)
	SSD SATA, 6 Gb/s, 1.2 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPDP (Drive Writes Per Day for 5 years)

	SSD SAS, 12 Gb/s, 960 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD (Drive Writes Per Day for 5 years)
	SSD SAS, 12 Gb/s, 960 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD (Drive Writes Per Day for 5 years)
	SSD SAS, 12 Gb/s, 800 GB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD (Drive Writes Per Day for 5 years), SED
	SSD SAS, 12 Gb/s, 800 GB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD (Drive Writes Per Day for 5 years)
	SSD SAS, 12 Gb/s, 480 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD (Drive Writes Per Day for 5 years)
	SSD SAS, 12 Gb/s, 480 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD (Drive Writes Per Day for 5 years)
	SSD SAS, 12 Gb/s, 400 GB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD (Drive Writes Per Day for 5 years), SED
	SSD SAS, 12 Gb/s, 400 GB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD (Drive Writes Per Day for 5 years)
	SSD SAS, 12 Gb/s, 400 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD (Drive Writes Per Day for 5 years)
	SSD SAS, 12 Gb/s, 3.84 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD (Drive Writes Per Day for 5 years)
	SSD SAS, 12 Gb/s, 3.84 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD (Drive Writes Per Day for 5 years)
	SSD SAS, 12 Gb/s, 3.2 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD (Drive Writes Per Day for 5 years)
	SSD SAS, 12 Gb/s, 1.92 TB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1 DWPD (Drive Writes Per Day for 5 years)
	SSD SAS, 12 Gb/s, 1.92 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD (Drive Writes Per Day for 5 years)
	SSD SAS, 12 Gb/s, 1.6 TB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD (Drive Writes Per Day for 5 years), SED
	SSD SAS, 12 Gb/s, 1.6 TB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD (Drive Writes Per Day for 5 years)
	SSD SAS, 12 Gb/s, 1.6 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD (Drive Writes Per Day for 5 years)
	DOM SATA, 6 Gb/s, 128 GB, non hot plug, enterprise, 0.13 DWPD (Drive Writes Per Day for 5 years)
	DOM SATA, 6 Gb/s, 128 GB, non hot plug, enterprise, 0.054 DWPD (drive writes per day for 5 years)
	DOM SATA, 6 Gb/s, 64 GB, non hot plug, enterprise, 0.14 DWPD (Drive Writes Per Day for 5 years)
	DOM SATA, 6 Gb/s, 64 GB, non hot plug, enterprise, 0.054 DWPD (drive writes per day for 5 years)
RAID Controller	Fujitsu PRAID EP420i, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 2 GB, Optional FBU based on LSI SAS3108
	Fujitsu PRAID EP420i for SafeStore, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 2 GB, Optional FBU based on LSI SAS3108
	Fujitsu PRAID EP400i, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 1 GB, Optional FBU based on LSI SAS3108
Fibre Channel controller	Fibre Channel Host Bus Adapter 2 x 32 Gbit/s Cavium QLE2742 MMF LC-style
	Fibre Channel Host Bus Adapter 2 x 32 Gbit/s Emulex LPe32002-M6-F MMF LC-style
	Fibre Channel Host Bus Adapter 2 x 16 Gbit/s Emulex LPe16002B LC-style
	Fibre Channel Host Bus Adapter 2 x 16 Gbit/s Qlogic QLE2672 LC-style
	Fibre Channel Host Bus Adapter 2 x 16 Gbit/s Qlogic QLE2692 LC-style
	Fibre Channel Host Bus Adapter 2 x 16 Gbit/s Emulex LPe31002-M6-F MMF LC-style
	Converged Network Adapter 1 x 40 Gbit/s PCIe 3.0 x8 QSFP+ ( Emulex )
	Converged Network Adapter 2 x 10 Gbit/s PCIe 3.0 x8 SFP+ ( Emulex )
Communication, Network	Ethernet Ctrl. 2 x 10 Gbit/s ; 1 Gbit/s PCIe 3.0 x8 RJ45 ( Intel® )
	Ethernet Ctrl. 2 x 10 Gbit/s PCIe 2.0 x8 SFP+ ( Fujitsu )
	Ethernet Ctrl. 2 x 10 Gbit/s PCIe 2.1 x8 RJ45 ( Intel® )
	Ethernet Ctrl. 2 x 10 Gbit/s PCIe 3.0 x8 10Gbit/s Eth (RJ45) ( Emulex )
	Ethernet Ctrl. 2 x 10 Gbit/s PCIe 3.0 x8 SFP+ ( Emulex )
Communication, Network	Ethernet Ctrl. 2 x 10 Gbit/s PCIe 3.0 x8 SFP+ ( Intel® )
	Ethernet Ctrl. 2 x 1 Gbit/s PCIe 2.1 x4 RJ45 ( Intel® )
	Ethernet Ctrl. 4 x 1 Gbit/s PCIe 2.1 x4 RJ45 ( Intel® )
	InfiniBand HCA 1 x 100 Gbit/s PCIe 3.0 x16 QSFP for the US market max. one IB HCA 100Gb controller can be installed ( Mellanox )
	InfiniBand HCA 1 x 40 Gbit/s PCIe 2.0 x8 QSFP ( Intel® )
	InfiniBand HCA 1 x 56 Gbit/s PCIe 3.0 x8 QSFP for the US market max. one IB HCA 56Gb controller can be installed ( Mellanox )
	InfiniBand HCA 2 x 100 Gbit/s PCIe 3.0 x16 QSFP for the US market max. one IB HCA 100Gb controller can be installed ( Mellanox )

	InfiniBand HCA 2 x 40 Gbit/s PCIe 2.0 x8 QSFP ( Intel® )
Communication, Network	InfiniBand HCA 2 x 56 Gbit/s PCIe 3.0 x8 QSFP for the US market max. one IB HCA 56Gb controller can be installed ( Mellanox )
	Omni Path 1 x PCIe 3.0 x16 ( Intel® )
Graphics add on cards (optional)	NVIDIA® Tesla® M60, 4096 cores, PCIe 3.0 x16
Graphics add on cards	NVIDIA® Tesla® P100, 3584 cores, PCIe 3.0 x16
Warranty	
Warranty type	Onsite warranty
Product Support Services - the perfect extension	
Recommended Service	24x7, Onsite Response Time: 4h - For locations outside of EMEA please contact your local Fujitsu partner.
Spare Parts availability	5 years
Service Weblink	<a href="http://ts.fujitsu.com/Supportservice">http://ts.fujitsu.com/Supportservice</a>



# More information

## Fujitsu platform solutions

In addition to Fujitsu PRIMERGY CX2570 M2, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

**Dynamic Infrastructures**  
With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

**Computing Products**  
[www.fujitsu.com/global/products/computing/](http://www.fujitsu.com/global/products/computing/)

**Software**  
[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

## More information

Learn more about Fujitsu PRIMERGY CX2570 M2, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.  
<http://www.fujitsu.com/PRIMERGY>

## Fujitsu green policy innovation

## Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.  
For further information see [http://ts.fujitsu.com/terms\\_of\\_use.html](http://ts.fujitsu.com/terms_of_use.html)  
Copyright © Fujitsu Technology Solutions

## Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

**Contact**  
FUJITSU LIMITED  
Mies-van-der-Rohe-Straße 8  
80807 München  
Germany  
Website: [www.ts.fujitsu.com](http://www.ts.fujitsu.com)  
2021-09-06 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.  
For further information see [http://ts.fujitsu.com/terms\\_of\\_use.html](http://ts.fujitsu.com/terms_of_use.html)  
Copyright © Fujitsu Technology Solutions