

Data Sheet

Fujitsu PRIMERGY RX4770 M4 Server

Power for the backend of digitalization

PRIMERGY RX4770 M4

The FUJITSU Server PRIMERGY RX4770 M4 is an industry-standard x86 server system with four sockets, providing superior levels of performance, scalability and efficiency. This combination turns the server into an ideal platform for running databases and transactional applications, business intelligence (BI) workloads, back-end and in-memory databases as well as other compute-intensive applications. In addition, it substantially simplifies carrying out DC server optimization such as server virtualization or consolidation. Featuring the latest Intel® Xeon® Scalable Family processors with each up to 28 cores pushes this server to a whole new level of compute performance to deliver more efficient business results. Thanks to the highly performant and superfast DDR4 memory technology with up to 6TB memory capacity along with excellent support for NVME Flash drives, the system can handle complex, data-intensive workloads such as in-memory databases like SAP HANA® and real-time business analytics even easier than the previous generation. The PRIMERGY RX4770 M4 supports 12 Gbit/s SAS/SATA controllers with optional FBU. It can either come as a 16x 2.5-inch hot-plug storage drives holding base unit or in a base unit holding a total of 12x storage drives even for directly connected PCIe SSDs. Up to eight PCI-Express Gen3 slots increases bandwidth and provides sufficient expandability for faster insights. With built-in redundancy and hot-pluggable components as well as advanced business-critical RAS features such as Resilient System- and Memory Technologies, the RX4770 M4 provides higher availability and uptime. Virtualization and consolidation of IT

resources offer many benefits but can often lead to increased expenses for server administration. Therefore the PRIMERGY RX4770 M4 delivers state-of-the-art management capabilities with the latest generation integrated Remote Management Controller (iRMC S5) offering a variety of user-friendly functions to ensure a faster and more cost-effective infrastructure management, no matter whether the server is located in the server-room next door or in another part of the world.



Features & Benefits

Main Features	Benefits
<p>Versatile Performance for any computing need</p> <ul style="list-style-type: none"> ■ 4x Intel® Xeon® Scalable family processors with up to 28 cores relying on Intel® UltraPath Interconnect for an increased data rate between the CPUs. ■ Up to 6,144 GB DDR4 memory with 2,666 MT/s (48 DIMM slots). ■ 8x PCIe Gen3 slots. <p>Enhanced Features for enhanced Computing</p> <ul style="list-style-type: none"> ■ Extended RAS-features for fail-safe operation: Built-in redundancy and hot-pluggable components, Advanced ECC, Memory Scrubbing and SDDC. ■ On Onboard LAN via OCP for basic LAN, DynamicLoM for extended requirements. ■ Ideal scalability of either up to 16x 2.5-inch HDD/SSD + 1x ODD or up to 12x PCIe 2.5-inch SSD SFF*. ■ Internal M.2 device support for hypervisor installations. ■ Redundant hot-plug power supply units with 94% energy efficiency. ■ Fujitsu's Cool-safe® Advanced Thermal Design for higher ambient temperatures in the data center, optional Liquid Cooling (on special request) for even more advanced computing. <p>Foundation for Trust and Security</p> <ul style="list-style-type: none"> ■ Fujitsu ServerView Suite including tools for installation and deployment, permanent status monitoring and control. ■ BIOS, firmware and selected software are updated free of charge. ■ TPM1.2 & 2.0 modules and latest operating system support. <p>Simplified management</p> <ul style="list-style-type: none"> ■ iRMC S5 comes with new interactive web UI and conforms to Redfish providing unified API support for heterogeneous environment. 	<ul style="list-style-type: none"> ■ Ready for the future and data growth scenarios with the performance of four processors – optimal for database processing. ■ DDR4 memories with higher bandwidth and lower consumption are the enabler; optimized for enormous data amounts in data centers and high performance computing. ■ Flexible expandability and diverse options for storage devices permits for the integration of existing and new SSD and HDD as needed. Less today, more in future – or vice versa. <p>Business-critical RAS features lowering the risk for unplanned IT downtimes. The systems' enhanced set of features adds even more reliability, availability, and serviceability that customers need for running their business-critical applications.</p> <ul style="list-style-type: none"> ■ The right Ethernet connection for all: Basic via onboard LAN, extended with DynamicLoM guarantees the highest flexibility to integrate the server into existing infrastructures – now and in future without overhauling the existing infrastructure. ■ Flexible expandability and diverse options for storage devices permits for the integration of existing and new SSD and HDD as needed. Less today, more in future – or vice versa. ■ Not only "greener", also less expensive over time: Highly efficient hot-plug power supplies save energy costs and make it easy to maintain the running system and ensure a 99,997% uptime. ■ Higher ambient temperatures lead to lower costs for cooling the data center. <ul style="list-style-type: none"> ■ Lifecycle investment protection. ■ The comprehensive tools of the FUJITSU ServerView Suite eases the administrators life. ■ Hardware and Software driven security features are very important in a fast-paced world, especially considering cybercrime. <ul style="list-style-type: none"> ■ Optimized for both: data centers and SMEs can now rely on latest generation iRMC S5 increasing security and server admin productivity.

Technical details

PRIMERGY RX4770 M4

Mainboard

Mainboard type	D3753
Chipset	Intel® C624
Processor quantity and type	2 or 4 x Intel® Xeon® Processor Scalable Family
Processor notes	A minimum of 2 processors must be configured, no mix of different processor types
Memory slots	48 (12 DIMMs per CPU, 6 channels with 2 slots per channel)
Memory slot type	DIMM (DDR4)
Memory capacity (min. - max.)	16 GB - 6 TB
Memory protection	Advanced ECC Memory Scrubbing SDDC Memory Mirroring support Rank sparing memory support
Memory notes	Memory Mirroring with identical modules in both channel pairs of a bank (6 modules per bank), Rank sparing or Performance Mode with identical modules in all six channels (6 modules per bank).

Interfaces

USB 3.x ports	5 x USB 3.0 (2x front, 2x rear, 1x internal)
Graphics (15-pin)	2 x VGA (1 x front, 1 x rear)
Serial 1 (9-pin)	1 x RS-232-C
Management LAN (RJ45)	1 x dedicated management LAN port for iRMC S5 (10/100/1000 Mbit/s) Management LAN traffic can be switched to shared onboard LAN controller port, speed and connector is related to installed interface card.

Onboard or integrated Controller

RAID controller	All hardware storage controller options are described under Components
SATA Controller	Intel® C624, 1 x SATA channel for ODD
LAN Controller	DynamicLoM based on Intel® C624 (Intel® X722) Optional DynamicLoM OCP adaptors: 2 x 10 Gbit/s Ethernet (RJ45) 2 x 10 Gbit/s SFP+ 4 x 1 Gbit/s Ethernet (RJ45) 4 x 10 Gbit/s SFP+ All supported features are described in relevant system configurator. Wake-on-LAN supported on onboard Port 1 and 2. Extra LAN controller(PCle Cards) are listed below. (i210 LAN card via project release possible)
Remote management controller	Integrated Remote Management Controller (iRMC S5, 512 MB attached memory incl. graphics controller) IPMI 2.0 compatible
Trusted Platform Module (TPM)	Infineon / TPM 1.2 or TPM 2.0 module; TCG compliant (option)

Slots

PCI-Express 3.0 x16	8 x whereas 4x full height and 4x low profile with up to 167mm length
Slot Notes	Important note: 4 PCIe slots are supported with the first and second processor. Additional 4 PCIe slots are supported with the third and forth processors. Slot 1&2: PCIe Gen3 x16 @CPU1 for low profile cards with up to 167mm length Slot 3&4: PCIe Gen3 x16 @CPU4 for full height cards with up to 167mm length Slot 5: PCIe Gen3 x16 @CPU2 for low profile cards with up to 167mm length Slot 6&7: PCIe Gen3 x16 @CPU3 for full height cards with up to 167mm length Slot 8: PCIe Gen3 x16 @CPU2 for low profile cards with up to 167mm length (used for the internal modular RAID controller if selected)

Drive bays

Storage drive bays	2.5-inch hot-plug SAS/SATA/PCle 2 x M.2 slot whereas slot 1 supports 80mm or 110mm and slot 2 supports 42mm or 80mm
Notes accessible drives	All possible options described in relevant system configurator.

Drive bays

Optional accessible drives	1 x 5.25/9.5mm for DVD-RW/Blu-ray
----------------------------	-----------------------------------

General system information

Number of fans	12
Fan configuration	hot-plug
Fan notes	11+1 redundant

Operating panel

Operating buttons	On/off switch NMI button Reset button ID button
Status LEDs	System status (green) Global error (orange) Identification (blue) Hard disks access (green) Power (green) CSS (orange) At system rear side: System status (green) CSS (orange) Identification (blue) Global error (orange) LAN connection (green) LAN speed (green / yellow)

BIOS

BIOS features	UEFI compliant Legacy BIOS compatibility customer configuration option Secure boot support ROM based setup utility GPT support for boot drives larger than 2.2 TB Memory Redundancy support (Mirroring, Sparing) IPMI support Recovery BIOS BIOS settings save and restore Local BIOS update from USB device Online update tools for main Linux versions Local and remote update via ServerView Update Manager IPv4/IPv6 remote PXE & iSCSI boot support
---------------	--

Operating Systems and Virtualization Software

Certified or supported operating systems
and virtualization software

Windows Server 2019 Datacenter
Windows Server 2019 Standard
Windows Server Datacenter, version 1809
Windows Server Standard, version 1809
Hyper-V Server 2016
Windows Server 2016 Datacenter
Windows Server 2016 Standard
Windows Server Datacenter, version 1709
Hyper-V Server 2012 R2
Windows Server 2012 R2 Datacenter
Windows Server 2012 R2 Standard
VMware vSphere™ 6.7
VMware vSphere™ 6.5
VMware vSphere™ 6.0
SUSE® Linux Enterprise Server 12
SUSE® Linux Enterprise Server 11
Red Hat® Enterprise Linux 8
Red Hat® Enterprise Linux 7
Red Hat® Enterprise Linux 6
Oracle® Linux 7
Oracle® Linux 6
Oracle® VM 3

Operating system release link <http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473>

Operating system notes Support of other Linux derivatives on demand

Infrastructure and Server Management

DC Infrastructure Management	Infrastructure Manager (ISM) Essential Edition Node Management Health status Monitoring and Control Capacity/Threshold Management Power Management Converged Management Auto Discovery Remote Management Update Management Logging and Auditing ServerView Suite (Deploy) ServerView Installation Manager ServerView Scripting Toolkit ServerView Suite (Control) ServerView Operations Manager (incl. PDA and ASR & R) ServerView Agents and CIM provider ServerView Agentless Management ServerView System Monitor SVOM- Event Manager ServerView RAID Manager SVOM- Threshold Manager Power Monitor (monitoring the Power Consumption) Power Management (iRMC) Storage Management (server) with SVOM/SV-RAID ServerView Suite (Maintain) iRMC S5 (Remote Management) System Update Manager (BIOS, Firmware, Windows Drives and SV Agents) Performance management (SVOM) Asset Management Primecollect Customer Self Service Online Diagnostics ServerView Suite (Integrate) ServerView Integration packs for MS System Center, VMware vCenter, VMware vRealize, Nagios, and HP SIM
Server Management	ServerView Suite (Maintain) ServerView eLCM iRMC Advanced Pack incl. Advanced Video Redirection (AVR), video capturing and Virtual Media Infrastructure Manager (ISM) Automate device configuration Mass OS installation Node Management Health status Monitoring and Control Capacity/Threshold Management Power Management Converged Management Auto Discovery Virtual-IO Management Network topology Management Remote Management Update Management Logging and Auditing Integrate in to Enterprise Management Vendor specific Management Monitor 3rd party platforms
Management notes	Regarding dependencies for ServerView Suite software products see dedicated product data sheets.
Dimensions / Weight	
Rack (W x D x H)	482.6 mm (Bezel) / 434.8 mm (Body) x 724.8 x 86.9 mm
Mounting Depth Rack	741.3 mm
Height Unit Rack	2 U
19" rackmount	Yes

Dimensions / Weight

Mounting Cable depth rack	200 mm (1,000 mm Rack recommended)
Weight	max. 30.3 kg
Weight notes	Actual weight may vary depending on configuration
Rack integration kit	Rack integration kit as option

Environment

Operating temperature note	Cool-safe® Advanced Thermal Design (above 35 °C or below 10 °C) depending on configuration. Please use the Fujitsu WebArchitect (www.fujitsu.com/configurator/public) to get detailed information on the corresponding configurations.
Operating relative humidity	10 - 85 % (non condensing)
Operating environment	FTS 04230 – Guideline for Data Center (installation specification)
Operating environment link	http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe
Noise emission	Measured according to ISO 7779 and declared according to ISO 9296
Sound pressure (LpAm)	47.4 dB(A) (idle) / 47.4 dB(A) (operating)
Sound power (LWAd; 1B = 10dB)	6.5 B (idle) / 6.5 B (operating)
Noise notes	Noise emissions depends on operation modes, system configuration and ambient temperature. Operating mode measured based on OLTIS with 50% load. *OLTIS = FUJITSU Load Profile which stresses all components of a server with a given load level.

Electrical values

Power supply configuration	2 hot-plug power supplies (standard), single power supply configuration possible
Hot-plug power supply redundancy	Optional
Active power (max. configuration)	2,189 W
Apparent power (max. configuration)	2213 VA
Heat emission (max. configuration)	7880.4 kJ/h (7469.2 BTU/h)
Rated current max.	20 A (100 V) / 8 A (240 V)
Active power note	To estimate the power consumption of different configurations use the Fujitsu Product Configurator: www.fujitsu.com/configurator/public
Power supply	1600W hot-plug, 94% (Platinum efficiency), 200-240V, 50 / 60Hz
Power supply notes	Hot plug power supply redundancy with AC input Voltage at 200 - 240V only

Compliance

Global	CB RoHS (Substance limitations in accordance with global RoHS regulations) WEEE (Waste electrical and electronical equipment)
Europe	CE
USA/Canada	CSAc/us ICES-003 / NMB-003 Class A FCC Class A
Japan	VCCI:V3 Class A + JIS 61000-3-2
South Korea	KN32 KN35
Australia/New Zealand	C-Tick (planned)
Taiwan	CNS 13438 class A - planned
Compliance link	https://sp.ts.fujitsu.com/sites/certificates
Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request. * Warning: This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.

Components

Optical drives	Blu-ray Disc™ Triple Writer, (6x BD-RW, 8x DVD, 24x CD), ultraslim, SATA I DVD Super Multi ultra slim , (8x DVD; 24x CD), ultraslim, SATA I
Drives	SSD SATA, 6 Gb/s, 480 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 0.9 DWPD SSD SATA, 6 Gb/s, 240 GB, Read-Intensive, hot-plug, 2.5-inch, enterprise, 1.4 DWPD SSD SATA, 6 Gb/s, 3.84 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD SSD SAS, 12 Gb/s, 800 GB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD SSD SAS, 12 Gb/s, 400 GB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD, SED SSD SAS, 12 Gb/s, 400 GB, Write-Intensive, hot-plug, 2.5-inch, enterprise, 10 DWPD PCIe-SSD SFF, 3.2 TB, Mixed-use, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD PCIe-SSD SFF, 2 TB, Read-Intensive, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD PCIe-SSD SFF, 1.6 TB, Mixed-use, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD PCIe-SSD SFF, 1 TB, Read-Intensive, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, 512e, hot-plug, 2.5-inch, business critical HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, 512e, hot-plug, 2.5-inch, business critical HDD SAS, 12 Gb/s, 900 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise HDD SAS, 12 Gb/s, 900 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise HDD SAS, 12 Gb/s, 900 GB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise HDD SAS, 12 Gb/s, 600 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise HDD SAS, 12 Gb/s, 300 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise HDD SAS, 12 Gb/s, 300 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise, SED HDD SAS, 12 Gb/s, 2.4 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise, SED HDD SAS, 12 Gb/s, 2.4 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise HDD SAS, 12 Gb/s, 2 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical HDD SAS, 12 Gb/s, 1.8 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, hot-plug, 2.5-inch, enterprise HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise HDD SAS, 12 Gb/s, 1 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical
	Fujitsu PSAS CP400i SAS Ctrl. 12 Gbit/s 8 ports int. PCIe 3.0 x8
RAID Controller	Fujitsu PRAID EP580i LP, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, NVMe-PCIe 8 Gbit/s, 8 Gbit/s 16 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 8 GB, Optional FBU based on LSI SAS3516 Fujitsu PRAID EP540i LP, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, NVMe-PCIe 8 Gbit/s, 8 Gbit/s 16 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 4 GB, Optional FBU based on LSI SAS3516 Fujitsu PRAID EP540e LP, RAID 5/6 Ctrl., SAS 12 Gbit/s, 8 ports ext. RAID level: 0, 1, 10, 5, 50, 6, 60, 4 GB, Optional FBU based on LSI SAS3516 Fujitsu PRAID EP540e FH, RAID 5/6 Ctrl., SAS 12 Gbit/s, 8 ports ext. RAID level: 0, 1, 10, 5, 50, 6, 60, 4 GB, Optional FBU based on LSI SAS3516 Fujitsu PRAID EP420i, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 2 GB, Optional FBU based on LSI SAS3108 Fujitsu PRAID EP420i for SafeStore, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 2 GB, Optional FBU based on LSI SAS3108 Fujitsu PRAID EP400i, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 1 GB, Optional FBU based on LSI SAS3108 Fujitsu PRAID CP400i, RAID Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 1E, 10, 5, 50, No FBU support

Fibre Channel controller	Fibre Channel Host Bus Adapter 1 x 32 Gbit/s Cavium QLE2740 MMF LC-style
	Fibre Channel Host Bus Adapter 2 x 32 Gbit/s Cavium QLE2742 MMF LC-style
	Fibre Channel Host Bus Adapter 1 x 32 Gbit/s Emulex LPe32000-M6-F MMF LC-style
	Fibre Channel Host Bus Adapter 2 x 32 Gbit/s Emulex LPe32002-M6-F MMF LC-style
	Fibre Channel Host Bus Adapter 1 x 16 Gbit/s Qlogic QLE2690 LC-style
	Fibre Channel Host Bus Adapter 2 x 16 Gbit/s Qlogic QLE2692 LC-style
	Fibre Channel Host Bus Adapter 1 x 16 Gbit/s Emulex LPe31000-M6-F MMF LC-style
	Fibre Channel Host Bus Adapter 2 x 16 Gbit/s Emulex LPe31002-M6-F MMF LC-style
Communication, Network	Ethernet Ctrl. 2 x 10 Gbit/s ; 1 Gbit/s PCIe 3.0 x8 RJ45 (Intel®)
	Ethernet Ctrl. 2 x 10 Gbit/s / 25 Gbit/s PCIe 3.0 x8 SFP28 (Intel®)
	Ethernet Ctrl. 2 x 10 Gbit/s / 25 Gbit/s PCIe 3.0 x8 SFP28 (Mellanox)
	Ethernet Ctrl. 2 x 10 Gbit/s PCIe 3.0 x8 SFP+ (Intel®)
	Ethernet Ctrl. 4 x 10 Gbit/s ; 1 Gbit/s PCIe 3.0 x8 RJ45 (Intel®)
	Ethernet Ctrl. 4 x 10 Gbit/s PCIe 3.0 x8 SFP+ (Intel®)
	Ethernet Ctrl. 4 x 1 Gbit/s PCIe 2.1 x4 RJ45 (Intel®)
	InfiniBand HCA 1 x 100 Gbit/s PCIe 3.0 x16 QSFP for the US market max. one IB HCA 100Gb controller can be installed (Mellanox)
	InfiniBand HCA 1 x 56 Gbit/s PCIe 3.0 x8 QSFP for the US market max. one IB HCA 56Gb controller can be installed (Mellanox)
	InfiniBand HCA 2 x 100 Gbit/s PCIe 3.0 x16 QSFP for the US market max. one IB HCA 100Gb controller can be installed (Mellanox)
	InfiniBand HCA 2 x 56 Gbit/s PCIe 3.0 x8 QSFP for the US market max. one IB HCA 56Gb controller can be installed (Mellanox)
	Interface modul for Dynamic LoM 2 x 10 Gbit/s RJ45 (Intel®)
	Interface modul for Dynamic LoM 2 x 10 Gbit/s SFP+ (Intel®)
Rack infrastructure	Interface modul for Dynamic LoM 4 x 10 Gbit/s SFP+ (Intel®)
	Interface modul for Dynamic LoM 4 x 1 Gbit/s RJ45 (Intel®)
	Omni Path 1 x PCIe 3.0 x16 (Intel®)
	Rackmount kit full extraction (820mm), tool less mounting, length variable 559-914mm
	Cable Management for 19-inch DataCenter / PRIMECENTER Racks
	Cable Arm 2U for PRIMECENTER- and 3rd-party racks
Warranty	
Warranty period	3 years
Warranty type	Onsite warranty
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty/Index.asp?LNG=COM
Product Support - the perfect extension	
Support Pack Options	Globally available in major metropolitan areas: 9x5, Next Business Day Onsite Response Time 9x5, 4h Onsite Response Time (depending on country) 24x7, 4h Onsite Response Time (depending on country)
Recommended Service	24x7, Onsite Response Time: 4h - For locations outside of EMEA please contact your local Fujitsu partner.
Service Lifecycle	at least 5 years after shipment, for details see https://support.ts.fujitsu.com/
Spare Parts availability	5 years
Service Weblink	http://ts.fujitsu.com/Supportservice

More information

Fujitsu platform solutions

In addition to Fujitsu PRIMERGY RX4770 M4, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures
With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products
www.fujitsu.com/global/products/computing/

Software
www.fujitsu.com/software/

More information

Learn more about Fujitsu PRIMERGY RX4770 M4, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
<http://www.fujitsu.com/global/products/computing/servers/primergy/rack/rx4770m4/>

Fujitsu green policy innovation

Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

Contact
FUJITSU LIMITED
Mies-van-der-Rohe-Straße 8
80807 München
Germany
Website: www.ts.fujitsu.com
2024-04-06 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions