Data Sheet
Fujitsu Display B24-9 TS

Widescreen 60.5 cm (23.8-inch) Advanced Ergonomic Display
Ideal for office applications and 24/7 usage

The FUJITSU Display B24-9 TS is a widescreen display with 1920 x 1080 Full HD resolution with a ultra-thin bezel housing. The monitor has a wide viewing angle that delivers consistent picture quality and DisplayView™ manageability software for further enhancing monitor features with a range of connectivity options ideal for medium- and large-sized businesses.





The 23.8-inch display with 16:9 aspect ratio at Full HD resolution for consistent clarity and superior viewing experience is ideal for office applications.

The 6-in-1 stand base allows users to tilt, swivel, adjust height and rotate monitor display as per their comfort and working style.

The Ultra-thin bezel housing on three sides for multi-monitoring scenarios and integrated speakers and cable guide allows for a clean desk experience.

The always available USB, DisplayPort, HDMI interfaces ensure to have a complete package that meets all your business requirements.

The ergonomic stand with height adjust with 345° swivel, 35° rear tilt and 45 mm picture over desk allow enhanced flexibility.

The environmental-friendly LED technology with highly efficient energy saving functions like ECO Operation mode and ECO standy help you save on costs.

The DisplayView software enables you to configure your monitor for adjusting screen brightness, pivot function and much more.

Technical details

Special features	
	In-Plane Switching (IPS) technology Low blue light mode 6-in-1 Stand Eco button for Eco mode and 3-coloured Eco status LED Always available USB (in operating and standby mode) DisplayView™ Software 24/7 usage Integrated speakers
Ergonomic stand	
Stand	6-in-1 Stand
Height adjust range	150 mm
Picture height over desk (min)	45 mm
Rotation to portrait	90°
Tilt angle	-5° / +35°
Swivel angle	345°
Picture performance	
Panel and backlit	In-Plane Switching (IPS) technology/LED
Screen Surface Treatment	Anti-glare, 3H hard coating
Contrast - typical	1,000:1
Contrast - advanced	20,000,000:1
Response time gray to gray typical	5 ms (in video mode)
Viewing angle (h/v) - typical	178°/178° CR10:1
Color performance	16.7 million colors
Brightness - typical	250 cd/m2
Size and resolution	
Aspect ratio	16:9
Diagonal Size	60.5 cm (23.8-inch)
Resolution (native)	1,920 x 1,080 pixel
Resolution (interpolated)	1,680 x 1,050 pixel, 1,440 x 900 pixel, 1,280 x 1,024 pixel, 1,280 x 720 pixel, 1,024 x 768 pixel, 800 x 600 pixel, 640 x 480 pixel
Picture size	527 x 296 mm
Pixel Pitch	0.2745 mm
Frequencies	
Horizontal	30 - 82 kHz
Vertical	48 - 76 Hz
Connectivity	
DisplayPort	1 x DisplayPort 1.2
HDMI	1 x HDMI 1.4
VGA/D-SUB	1 x D-SUB
Audio signal output	3.5 mm stereo phone jack for head phone
Audio sound output	2 x 2 W
Audio signal input	3.5 mm stereo phone jack
USB downstream	2x USB 3.2 Gen1
USB upstream	1 x USB 3.2 Gen1
Ease-of-use menu	
Direct Access Keys	Brightness, ECO, Input, Mode, Audio, Menu
Languages	Arabic, Czech, Danish, Dutch, English, Finnish, French, German, Italian, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Japanese, Chinese simply, Chinese traditional
Brightness / Contrast	Brightness, Contrast, Black level, Auto level, ACR
Mode	sRGB, Office, Photo, Video, Low Blue Light
Color	sRGB, 5000K, 6500K, 7500K, Native, Custom Color (R,G,B)

OSD	Language, OSD-Timeout, OSD rotation
Image adjust	Clock, Phase, H-Position, V-Position, Expansion, Sharpness
Audio	Mute, Volume, Input for HDMI and DP interface
Information	Model name, Serial number, Signal input, Resolution/mode, Display mode , Color Temperature, ACR Status
Advanced settings	Overdrive, DDC/CI, Factory Recall
Power consumption (typical, w/o sound)	
Soft switch off	0.1 W
Power save mode	0.17 W
Operating with EPA settings	14.25 W
Total Energy Consumption (ETEC)	44.66 kWh/year
Operating maximum brightness	22 W
Power supply	integrated
Power notes	Speakers off, USB not connected ETEC and EPA refer to ENERGY STAR® 8.0
Electrical values	
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Protection class	1
Compliance	
Model	DY24-9T
Global	ENERGY STAR® 8.0, TÜV Low Blue Light Certified, TÜV Flicker Free Certified, Zero bright and dark pixel faults, Subpixel faults according to ISO9241-307 (Pixel fault class I), EPEAT® Silver (dedicated regions), TCO Certified
Europe	EN 62368-1, CE certification according to EC Directive 2004/108/EEC, RoHS, WEEE, IT-Eco-Declaration
Australia/New Zealand	RCM
China	CCC
Germany	TÜV GS
Russia	EAC
Singapore	S-Mark
South Korea	KC
Taiwan	BSMI
USA/Canada	FCC Class B, cTUVus
Compliance link	https://sp.ts.fujitsu.com/sites/certificates
Dimensions / Weight / Environmental	
Dimension without stand (W x D x H)	540.3 x 64 x 325.6 mm
	21.27 x 2.52 x 12.82 inch
Dimension with stand (W x D x H)	540.3 x 229.4 x 346.2 mm
	21.27 inch x 9.03 x 13.63 inch
Weight (unpacked)	5.25 kg
	11.57 lbs
Weight (Monitor only)	3.21 kg
	7.08 lbs
Operating ambient temperature	5 - 35 °C (41 - 95 °F)
Operating relative humidity	10 - 85 % (non condensing)
Miscellaneous	
Miscellaneous	VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared
Color	Matt black
Additional Software	
Additional software (optional)	WINDOWS WHQL driver DisplayView Suite
Additional software (notes)	Use of accompanying and/or additional Software is subject to proactive acceptance of the respective License Agreements /EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration.

Package content		
Display delivered accessories	DisplayPort data cable 1.8 m USB-cable 1.8 m (USB-A to USB-B) Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m Quickstart flyer Safety notes	
Display delivered accessories notes	Power cable with IEC-60320-C13, 3-pin connector on display side Data cables and USB cable detachable on display User manual and DisplayView Software is available via download	
Packaging dimension (mm)	655 x 411 x 220 mm	
Packaging dimension (inch)	25.79 x 16.18 x 8.66 inch	
Weight (packed)	7.1 kg	
Weight (packed) (lbs)	15.65 lbs	
Order information		
Order Code	S26361-K1643-V160	S26361-K1713-V160
EAN Code	4059595551776	4065221888277
Country specific order code	BDL:K1713V160-UK - with UK power cable, mandatory for Arabian countries BDL:K1713V160-CHN - with China power cable and CEL, mandatory for China BDL:K1713V160-INT - W/o power cable, mandatory for countries where import with EU cable is not allowed	
Accessories information	Further helpful options: Stands and Mounting kits: http://www.fujitsu.com/fts/products/computing/peripheral/accessories/desktop/ums/index.html Available Adapters: http://globalsp.ts.fujitsu.com/dmsp/Publications/public/pos-connectivity.pdf	
Warranty		
Warranty period	3 years (depending on country)	
Warranty Terms & Conditions	http://www.fujitsu.com/warranty	
Digital bug fixes	Subject to availability and following their generic release for the product, bug fixes and function-preserving patches for product-related software (firmware) can be downloaded from the technical support at: https://support.ts.fujitsu.com/ free of charge by entering the respective product serial number. For application software supplied together with the product, please directly refer to the support websites of the respective software manufacturer.	
Spare Parts availability	at least 7 years after shipment, for details see https://support.ts.fujitsu.com/	
Service Weblink	http://www.fujitsu.com/emeia/products/product-support-services/	

More information

Fujitsu products, solutions & services

In addition to Fujitsu Display B24-9 TS, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio
Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products
www.fujitsu.com/global/products/computing/

Software
www.fujitsu.com/software/

More information

Learn more about Fujitsu Display B24-9 TS, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/emeia/products/computing/peripheral/displays

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.
Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.
Please find further information at http://www.fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see https://www.fujitsu.com/global/about/resources/terms/
Copyright 2024 Fujitsu Technology Solutions GmbH

Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering.
Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.
The overall product has been designed and manufactured for general office use, regular personal use and ordinary industrial use.

CONTACT
Fujitsu Technology Solutions GmbH
Website: www.fujitsu.com
2024-03-06 EM-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see https://www.fujitsu.com/global/about/resources/terms/
Copyright 2024 Fujitsu Technology Solutions GmbH