

# Data Sheet

## Fujitsu PRIMEQUEST 3800E

### Redefining mission-critical server architecture

#### PRIMEQUEST 3800E

The FUJITSU Server PRIMEQUEST 3800E is purpose-built to optimize efficiency while maximizing performance and uptime in the most demanding mission-critical environments. It unifies the economic and flexibility benefits of x86 industry standard systems with mission-critical uptime features. The PRIMEQUEST 3800E dramatically simplifies server architecture for mission-critical computing and comes in an all-new compact 7U form factor. This octo-socket server features the latest Intel® Xeon® Platinum processors with up to 28 cores per processor for a total of 224 cores and delivers superior compute performance leading to efficient business results. With high capacity 12TB DDR4 memory at 2,666 MHz, populated over 96 DIMM slots, the system can support large amounts of data for in-memory databases such as SAP HANA®, real-time data analytics. The PRIMEQUEST 3800E provides enhanced performance in a significantly smaller form factor, resulting in lower power consumption and helps reduce the environmental footprint in a data center leading to significant cost savings. Moreover, the advanced reliability, availability and serviceability (RAS) features makes this server a robust and cost-effective solution for mission-critical environments. Customers running SAP, financial or big data applications will thus continuously benefit from a radically optimized cost effectiveness compared to UNIX®/Mainframe-based enterprise platforms, while preserving all the RAS qualities so that the system always remains active. The PRIMEQUEST 3800E is an ideal choice for high-volume, high-value workloads such as online transaction processing (OLTP), batch processing, and database applications.

Mission-critical features of the 3800E also enable outstanding platform reliability with innovative error prevention and self-healing capabilities, such as a Reserved System Board, flexible I/O as well as physical hardware partitioning (PPAR). With Reserved System Board, recovery from System Board failures happens in a matter of minutes. Moreover, unique features, such as Dynamic Reconfiguration enable the efficient use of available resources while simplifying resource management without any need for a reboot of the system. Therefore, the PRIMEQUEST 3800E is an ideal target platform for critical UNIX workloads/ UNIX migrations that require inherent robustness built in to the system.



# Features & Benefits

Main Features	Benefits
<p>Dynamic, scalable platform for the most demanding mission-critical environments</p> <ul style="list-style-type: none"><li>■ 8x Intel® Xeon® Platinum processors with up to 224 cores</li><li>■ Huge memory capacity of 12TB (DDR4, 2,666 MHz) over 96 DIMMs</li><li>■ Many I/O expansion options for up to 56 PCIe slots</li><li>■ Compact 7U form-factor</li><li>■ 'Glue-less' design, no external UPI cables</li><li>■ Economic scaling from 2 to 8 sockets</li></ul>	<ul style="list-style-type: none"><li>■ Unprecedented performance and memory capacity for high-volume, high-value workloads such as online transaction processing (OLTP), batch processing, and database applications</li><li>■ Fast memory and I/O throughput ensured</li><li>■ Cost-efficient 7U chassis packs superior performance in an economic, space-saving footprint</li><li>■ No external UltraPath Interconnect (UPI) cables ensure a high level of serviceability</li><li>■ This system is designed to enable simple scale-up as required components are "inside" the system thanks to the "glue-less" system design</li></ul>
<p>Mission critical uptime leads to highest availability values in the x86 industry standard</p> <ul style="list-style-type: none"><li>■ Different partitioning available: From software partitioning to completely isolated physical partitioning (PPAR)</li><li>■ Up to four physical partitions (PPAR): Failures of one partition do not influence other partitions</li><li>■ Active reserved system board for fast automatic recovery of services, in many cases without downtime</li><li>■ Flexible I/O ensures availability of PCIe devices</li><li>■ Almost everything is redundant</li><li>■ Online maintenance</li></ul>	<ul style="list-style-type: none"><li>■ Flexible platform to best meet individual requirements</li><li>■ Business continuity ensured even if there is a failure in one of the partitions</li><li>■ Its built-in error prevention/correction and self-healing capabilities result in outstanding platform reliability</li><li>■ All serviceable system modules can be accessed from the front or rear of the system without any cabling hassle. Moreover, Dynamic Reconfiguration enables online maintenance without the need for restarts or planned downtimes</li></ul>
<p>Cost efficiency for your data center</p> <ul style="list-style-type: none"><li>■ Combines x86 industry standard with mission-critical features</li><li>■ Compact 7U form-factor</li></ul>	<ul style="list-style-type: none"><li>■ Unity of x86 efficiency and flexibility with mission-critical availability; Eliminate costs related to the UNIX world</li><li>■ Enhanced performance in a significantly smaller form factor; Lower power consumption and helps reduce the environmental footprint in a data center leading to significant cost savings</li></ul>

# Technical details

## PRIMEQUEST 3800E

Mainboard type	up to 4 x Systemboards
Chipset	Intel® C621
Processor quantity and type	2, 4, 6, 8
Memory slots	96 Max. 12 TB
Memory slot type	DIMM (DDR4)
Memory capacity (min. - max.)	16 GB - 12 TB
Memory protection	ECC Advanced ECC Memory Mirroring support Address Range Memory Mirroring support Rank sparing memory support Memory Scrubbing SDDC+1 ADDDC-MR
Memory notes	Up to 96 DIMM slots per server within 4 system boards.
Memory modules notes	Memory modules will be delivered in set's of 2 DIMMs per order code
<b>Interfaces</b>	
USB 3.x ports	4 (up to 16 x USB, 4 x USB per Partition)
Graphics (15-pin)	1 x VGA per partition
Management LAN (RJ45)	Dedicated Service LAN port for MMB (10/100 Mbit/s)
<b>Onboard or integrated Controller</b>	
LAN Controller	Intel® X540-AT2 2 x 10 Gbit/s Ethernet (RJ45) 2 ports /IOU, up to 8 ports, TCP/IP acceleration, PXE boot via LAN from PXE server, iSCSI boot (also diskless) via onboard LAN
Remote management controller	PQ3000 Management Board (MMB)
<b>Slots</b>	
PCI-Express 3.0 x8	12 x Low profile (3slots / IOU, Max. 4 IOUs / Chassis)
PCI-Express 3.0 x16	4 x Low profile (1slot / IOU, Max. 4 IOUs / Chassis)
<b>Service Processor</b>	
General	Management Board (MMB), located on the rear side of the system. 2nd MMB as option
Interfaces	For Maintenance: - Local: 10/100M RJ45 for local maintenance. - Remote: 10/100M RJ45 for REMCS, AIS-Connect, ACA and ServiceLink connection (Remote monitoring service). For Management - 0/1 10M/100M/1G RJ45
Redundancy	2nd MMB as option
<b>Drive bays</b>	
Storage drive bays	2.5-inch hot-plug SAS
Storage drive bay configuration	Max. 24 x 2.5-inch
<b>General system information</b>	
Number of fans	6
Fan configuration	hot-plug
<b>Operating panel</b>	
Status LEDs	System status (orange / yellow) Power (amber / green) Identification (blue)

**RAS Features**

Standard	SDDC+1, ECC, redundant fans and power supply
Advanced	Intra-socket memory mirroring, MCA, ADDDC-MR
Mission-Critical	Physical Partition, Extended Partition, Reserved Systemboard, flex IO, Dynamic Reconfiguration, redundant MMB, hot-plug PCIe

**Operating Systems and Virtualization Software**

Operating system release link	<a href="http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473">http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473</a>
Operating system notes	Not all OSes, OS versions and server functions will be released at server release. For details refer to link below.

**Infrastructure and Server Management**

DC Infrastructure Management	ServerView Suite - Maintain Remote Management (iRMC) Update Management (BIOS, Firmware, Windows Drives and SV Agents) Performance Measurement Asset Management Online Diagnostics ServerView Suite (Integrate) ServerView Integration packs for MS System Center, VMware vCenter, VMware vRealize, Nagios and HP SIM Deployment tools and others ServerView Suite - Deploy SV Installation Manager ServerView Suite - Control Operations Manager Agents and CIM Providers / Agentless Service System Monitor RAID Manager Capacity Management Storage Support
Server Management	ServerView embedded Lifecycle Management (eLCM) Lifecycle management Infrastructure Manager (ISM) Automate device configuration Mass OS installation Node Management Health status Monitoring and Control Capacity/Threshold Management Power Management Converged Management Auto Discovery Virtual-IO Management Network topology Management Remote Management Update Management Logging and Auditing Integrate in to Enterprise Management Vendor specific Management Monitor 3rd party platforms

**Dimensions / Weight**

Rack (W x D x H)	445 x 820 x 308 mm
Height Unit Rack	7 U
19" rackmount	Yes
Weight	Up to 110 kg
Weight notes	Fully assembled Actual weight may vary depending on configuration

**Environment**

Operating ambient temperature	5 - 40 °C (41 - 104 °F)
Operating relative humidity	10 - 80 %
Temperature and humidity notes	Non condensing

**Environment**

Maximum altitude	3.000 m
Operating environment	FTS 04230 – Guideline for Data Center (installation specification)
Operating environment link	<a href="http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe">http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe</a>
Noise emission	Measured according to ISO 7779 and declared according to ISO 9296
Sound pressure (LpAm)	65dB
Sound power (LWAd; 1B = 10dB)	7.5B

**Electrical values**

Power supply configuration	Up to 4 hot-plug power supplies. Base unit equipped with 2 power supplies, redundancy as option.
Power supply efficiency	94 % (80 PLUS platinum)
Hot-plug power supply redundancy	Yes
Rated voltage range	200 V - 240 V
Rated frequency range	47 Hz - 63 Hz
Rated current max.	12A
Rated current in basic configuration	10A
Active power (max. configuration)	5,900 W
Heat emission (max. configuration)	21240.0 kJ/h (20131.6 BTU/h)

**Compliance**

Product	PRIMEQUEST 3800E
Model	MCJyAxxxx
Global	CB RoHS (Substance limitations in accordance with global RoHS regulations) WEEE (Waste electrical and electronic equipment) - planned
Europe	CE Class A *
Japan	VCCI
Compliance link	<a href="https://sp.ts.fujitsu.com/sites/certificates">https://sp.ts.fujitsu.com/sites/certificates</a>
Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request. * Warning: This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.

# Components

<b>Hard disk drives</b>	HDD SAS, 12 Gb/s, 900 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 900 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 600 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 300 GB, 15,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 300 GB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 1.8 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
	HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, 512n, hot-plug, 2.5-inch, enterprise
<b>PCIe SSD &amp; SATA DOM SSD</b>	PCIe-SSD SFF, 3.2 TB, Mixed-use, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD
	PCIe-SSD SFF, 1.6 TB, Mixed-use, hot-plug, 2.5-inch, Flash drive, 3.0 DWPD
<b>RAID Controller</b>	Fujitsu PRAID EP580i LP, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, NVMe-PCIe 8 Gbit/s 16 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 8 GB, Optional FBU based on LSI SAS3516
	Fujitsu PRAID EP540i LP, RAID 5/6 Ctrl., SAS/SATA 12 Gbit/s, NVMe-PCIe 8 Gbit/s 16 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 4 GB, Optional FBU based on LSI SAS3516

Fibre Channel controller	Fibre Channel Host Bus Adapter 1 x 16 Gbit/s Emulex LPe31000-M6-F MMF LC-style
	Fibre Channel Host Bus Adapter 2 x 16 Gbit/s Emulex LPe31002-M6-F MMF LC-style
	Fibre Channel Host Bus Adapter 1 x 32 Gbit/s Cavium QLE2740 MMF LC-style
	Fibre Channel Host Bus Adapter 2 x 32 Gbit/s Cavium QLE2742 MMF LC-style
	Fibre Channel Host Bus Adapter 1 x 32 Gbit/s Emulex LPe32000-M6-F MMF LC-style
	Fibre Channel Host Bus Adapter 2 x 32 Gbit/s Emulex LPe32002-M6-F MMF LC-style
	Fibre Channel Host Bus Adapter 1 x 16 Gbit/s Qlogic QLE2690 LC-style
	Fibre Channel Host Bus Adapter 2 x 16 Gbit/s Qlogic QLE2692 LC-style
Communication, Network	Ethernet Ctrl. 2 x 10 Gbit/s / 25 Gbit/s PCIe 3.0 x8 SFP28 ( Mellanox )
	Ethernet Ctrl. 2 x 10 Gbit/s PCIe 3.0 x8 RJ45 ( Intel® )
	Ethernet Ctrl. 2 x 10 Gbit/s PCIe 3.0 x8 SFP+ ( Intel® )
	Ethernet Ctrl. 4 x 1 Gbit/s PCIe 2.1 x4 RJ45 ( Intel® )
Warranty	
Product Support - the perfect extension	

# More information

In addition to Fujitsu PRIMEQUEST 3800E, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

**Dynamic Infrastructures**  
With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

**Computing Products**  
[www.fujitsu.com/global/products/computing/](http://www.fujitsu.com/global/products/computing/)

**Software**  
[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

More information

Learn more about Fujitsu PRIMEQUEST 3800E, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.  
<http://www.fujitsu.com/fts/products/computing/servers/mission-critical/primequest-3800e/>

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.  
Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.  
Please find further information at <http://www.fujitsu.com/global/about/environment/>

Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.  
For further information see [http://ts.fujitsu.com/terms\\_of\\_use.html](http://ts.fujitsu.com/terms_of_use.html)  
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.