Fujitsu recommends Windows 11 Pro.



Data Sheet Fujitsu Desktop ESPRIMO D7013

Small form factor PC in a more compact and space-saving design

The Fujitsu ESPRIMO D7013 is a high performance, secure small form factor 8 liters Desktop PC. Ultimate expandability, along with best-in-class connectivity and faster operations to create the perfect working desk. Options for flexible I/O port offers best connectivity and an 80Plus PLATINUM power supply forms great energy efficiency and continues operation for 5 years.

Latest Intel® chipset technology and higher memory speed High performance ensures faster operations and lower system response time

- Intel® Q670 chipset with higher memory frequency of 4,400 MT/s
- Intel® vPro™ Enterprise and Intel® vPro™ Essentials technology as BTO (depending on processor)

Ultimate expandability with easy serviceability Space saving design for your modern computing needs

- 3x low profile (LP) PCIe slots
- Space saving in width and depth with 8.3 liters volume
- Tool-less access to components, easy change and screw-less add on cards

Best-in-class connectivity

Be flexible and stay productive in a hyper-connected world

- Support of USB Type-C in front
- Flexiport options (VGA, DVI-D, HDMI, Type-C, DP, Serial LAN, 2x USB Type-A)
- Legacy PS2, serial port connectors as option

High security with integrated options

Designed to protect data and hardware components against manipulation and the ft $\,$

- Cable cover in addition to existing Smartcard reader, Erasedisk software
- Integrated cabinet lock with master key option
- Hole for pad lock and Kensington as standard for security

Low power consumption and environmental impact

Reduced environmental impact and reduced energy bills

- 80Plus GOLD and 80Plus PLATINUM power supply efficiency with monitor outlet
- Sum of post-consumer recycled content for plastic per weight is 61% (18% are from ITE derived post-consumer material and 43% are any other post-consumer material)













Components

	ESPRIMO D7013	ESPRIMO D7013 ESTAR
Processor	GHz, 18 MB, Intel® UHD Graphics 770) * Intel® Core™ i5-12400 processor (6 Cores / 12 Threads, 2.5 GHz, 18 MB, Intel® UHD Graphics 730) * Intel® Core™ i3-13100 processor (4 Cores / 8 Threads, 3.4 GHz, 12 MB, Intel® UHD Graphics 730) * Intel® Pentium® Gold G7400 (2 Cores / 4 Threads, 3.7 GHz, 6 MB, Intel® UHD Graphics 710)	
	Intel® vPro® Platform Logo (optional) with Intel® Core™ i5-12500, Intel® Core™ i5-13500, Intel® Core™ Core™ i9 processors *with Intel® Turbo Boost Technology 2.0 (clock speed and performance will vary depending on work variables) **with Intel® Turbo Boost Max Technology 3.0 (clock speed and performance will vary depending on other variables)	
Operating systems		
Operating system pre-installed	Windows 11 Pro. Fujitsu recommends Windows 11 Pro for business. Windows 11 Home	
Operating system compatible	Windows 10 Pro. Fujitsu recommends Windows 11 Pro for business.	
Operating system notes	Windows 11 requires for first device setup: - Internet connectivity - Microsoft account for Home editions or organizational account (e.g. ADD) for Pro editions After product end of life, Fujitsu continues to test and support new Windows releases for max. 5 years, extension of hardware services through warranty top ups. For more details please visit our Fujitsu Service Statement under https://support.ts.fujitsu.com/IndexPrasp?Ing=com&OpenTab= The use of Windows Operating System is subject to acceptance of the End User License Agreement of Napplicable under the relevant Microsoft program.	
	ESPRIMO D7013	ESPRIMO D7013 ESTAR
Memory modules	16 GB (1 module(s) 16 GB) DDR5, 4,800 MT/s, UDIMM 8 GB (1 module(s) 8 GB) DDR5, 4,800 MT/s, UDIMM	
	ESPRIMO D7013	ESPRIMO D7013 ESTAR
Graphics	Entry 3D: NVIDIA® T400, 4 GB, PCIe x16, 3 x miniDP Others: MiniDP to DP Adapter Cable	
	ESPRIMO D7013	ESPRIMO D7013 ESTAR
Mass storage 3.5 inch size	HDD SATA III, 7,200 rpm, 2000 GB, 3.5-inch	
Mass Storage M.2 technology	SSD PCIe, 1024 GB M.2 NVMe module (Gen4), SED SSD PCIe, 2048 GB M.2 NVMe module (Gen4), SED SSD PCIe, 256 GB M.2 NVMe Module (Gen4), Value, SED SSD PCIe, 512 GB M.2 NVMe module (Gen4), SED SSD PCIe, 512 GB M.2 NVMe Module (Gen4), Value, SED	
Hard disk notes	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. SSD (Solid State Disk) SED (Self-Encrypting Drive) Durability in accordance with the manufacturer's indications on read and write cycles.	

	ESPRIMO D7013	ESPRIMO D7013 ESTAR
Optical drive	BD Triple Writer SATA ultra slim (tray), SATA DVD Super Multi ultra slim (tray), SATA SD Card reader, USB 3.0	
	ESPRIMO D7013	ESPRIMO D7013 ESTAR
Interfaces add on cards / components	Parallel Card (1 Port) Intel® Wi-Fi 6E AX211 (2x2/160) Gig+ and Bluetooth 5.2; SRD cat.1 (dedicated regions only) Intel® Wi-Fi 6E AX211 (2x2/160) Gig+ and Bluetooth 5.2 vPro; SRD cat.1 (dedicated regions only) Dual serial card PCle x1 LP Dual 2.5 Gigabit Ethernet PCle x1 2.5 Gigabit Ethernet PCle x1	Intel® Wi-Fi 6E AX211 (2x2/160) Gig+ and Bluetooth 5.2; SRD cat.1 (dedicated regions only) Intel® Wi-Fi 6E AX211 (2x2/160) Gig+ and Bluetooth 5.2 vPro; SRD cat.1 (dedicated regions only)
LAN Notes	WI-FI 6E: The device does not operate in 6GHz band in all countries, due to national regulations. see flexible interface options Bluetooth 5.2: Bluetooth® 5.2 operation requires Microsoft OS support. Until Microsoft OS support is available, Bluetooth® 5.2 will function as Bluetooth® 5.1 or lower	
	ESPRIMO D7013	ESPRIMO D7013 ESTAR
Component notes	The listed product components and optional functions are not available in all region/countries	The listed product components and optional functions are not available in all region/countries; Energy Star certification only with Windows operating system Base unit for TCO Certified generation 9

Base unit

Base unit	ESPRIMO D7013	ESPRIMO D7013 ESTAR
Mainboard		
Mainboard type	D4022-A3x	
Formfactor	proprietary	
Chipset	Intel® Q670	
Processor socket	LGA1700	
Processor quantity maximum	1	
Supported capacity RAM (max.)	128 GB	
Memory slots	4 DIMM (DDR5)	
Memory frequency	4,400 MT/s	
Memory notes	4400 MT/s may be clocked down t Configuration with 3 (out of max. 4	nemory modules have to be ordered. Capacity per channel has to be the same. to 4000/3600 MT/s depending on processor and memory configuration by modules should be avoided because of performance limitations be avoided because of performance limitations
LAN	10/100/1,000 MBit/s Intel® I219LM	
Integrated WLAN	1 (optional with two integrated an	tennas)
BIOS version	AMI Aptio V UEFI Specification 2.8	
BIOS features	BIOS Flash EPROM update by softv Recovery BIOS Unified Extensible Firmware Interf	
Audio type	On board	
Audio codec	Realtek ALC897	
Audio features	Internal speaker supports audio pl	ayback, High Definition audio, 5.1 surround sound
I/O controller on board		
Serial ATA total	5	

I/O controller on board			
Controller functions	Serial ATA III (6 Gbit)		
Controller functions	NCQ		
	AHCI		
	SATA RAID Support		
Interfaces			
Audio: line-in	1	1	
Audio: line-out	1	1	
Front audio: headset	1	1	
Flexible Interface Options	One of following flexible Interface options can be added to the system	One of following flexible Interface options can be added to the system	
	HDMI™ (supports 4k@60Hz as specified in HDMI™ 2.1) DisplayPort™ 1.4a (external HDMI- and DVI adapters not supported) DVI-D VGA	HDMI [™] (supports 4k@60Hz as specified in HDMI [™] 2.1) DisplayPort [™] 1.4a (external HDMI- and DVI adapters not supported) DVI-D VGA	
	USB 3.2 Gen 2 (10 Gbps) Type-C [™] (supports DisplayPort [™] 1.4 and power delivery (PD) up to 15W) 2.5 Gigabit Ethernet (Intel 225LM)	USB 3.2 Gen 2 (10 Gbps) Type-C [™] (supports DisplayPort [™] 1.4 and power delivery (PD) up to 15W) 2.5 Gigabit Ethernet (Intel 225LM)	
	2x USB 2.0 Type A Serial port (9pin, 16 byte FIFO, 16550 compatible)	2x USB 2.0 Type A Serial port (9pin, 16 byte FIFO, 16550 compatible)	
USB front	2x USB 2.0 Type-A	2x USB 2.0 Type-A	
	2x USB 3.2 Gen 2 (10 Gbps) Type-A	2x USB 3.2 Gen 2 (10 Gbps) Type-A 1x USB 3.2 Gen 2x2 (20 Gbps) Type-C (supports up to 15W)	
USB rear	2x USB 2.0 Type-A	2x USB 2.0 Type-A	
	2x USB 3.2 Gen 1 (5 Gbps) Type-A	2x USB 3.2 Gen 1 (5 Gbps) Type-A	
	2x USB 3.2 Gen 2 (10 Gbps) Type-A see flexible interface options	2x USB 3.2 Gen 2 (10 Gbps) Type-A see flexible interface options	
USB internal	1x USB 2.0 or 1x USB 3.2 Gen 2 (10Gbps) Type-A	1x USB 2.0 or 1x USB 3.2 Gen 2 (10Gbps) Type-A	
DisplayPort	2 (DisplayPort 1.4; DP++)	2 (DisplayPort 1.4; DP++)	
Ethernet (RJ-45)	1	1	
Interface Module notes	Anytime USB charge functionality	Anytime USB charge functionality	
Kensington Lock support	1	1	
Input device / components			
Input devices (optional)	Keyboard		
	Mouse		
Drive bays			
Drive bays total	3		
2.5-inch internal bays	1		
5.25-inch external bays	1		
Drive bay notes	optional: 1x internal 3.5" bay (screwless) can be used via adapter for 1x or 2x 2.5" drives (screwless); 5.25" bay: for slim optical disc drive only;		
M.2-2280	2 x On mainboard for SSD NVMe (PCle 4.0 x4; up to 64Gbit/	2 x On mainboard for SSD NVMe (PCIe 4.0 x4; up to 64Gbit/s)	
Slots			
PCI-Express 3.0 x1	1 x (110 mm / 4.33 inch) Low profile		
PCI-Express 4.0 x16	1 x (210 mm / 8.27 inch) Low profile		
PCI-Express 4.0 x4 (mech. x16)	1 x (150 mm / 5.91 inch) Low profile		
M.2-2230	on mainboard for WLAN module		
Graphics on board			
Graphics brand name	Intel® UHD Graphics 770, Intel® UHD Graphics 730, Intel® UHD Graphics 710		
Shared video memory	Up to half size of total system memory		
TFT resolution (VGA)	Up to 1,920 x 1,080 pixel		
TFT resolution (DVI)	Up to 1,920 x 1,200 pixel		
TFT resolution (DisplayPort)	Up to 4,096 x 2,304 pixel		
TFT resolution (HDMI)	Up to 4,096 x 2,304 pixel		

Graphics on board		
Graphics features	Support for up to four independent displays DirectX® 12.1 HDCP support OpenCL 3.0 OpenGL® 4.6 Vulkan™ For multi monitoring mode, graphics card and integrated graphics run in parallel DisplayPort interface supports Ver. 1.4 incl. Multi-Stream Digital audio formats are supported, including Dolby Digital Plus (7.1 channels) DVI-D interface supports audio output if connected to the HDMI interface of a display via suitable adapter cables (no included) see flexible interface options	
Base unit	ESPRIMO D7013 ESPRIMO D7013 ESTAR	
Electrical values		
Power efficiency note	Power supply efficiency in % at 10% / 20% / 50% / 100% load 80Plus GOLD: for 230V; 87/90/92/91 for 115V; 86/89/91/88 80Plus PLATINUM: for 230V; 88/92/94/93 for 115V; 87/91/92/91	
Rated voltage range	100 V - 240 V	
Rated frequency range	50 Hz - 60 Hz	
Operating voltage range	90 V - 264 V	
Operating line frequency range	47 Hz - 63 Hz	
Max. output of single power supply	GOLD: 280W; PLATINUM: 300 W	
Power factor correction/active power	active	
Monitor outlet	Switched for PLATINUM power supply	
Base unit	ESPRIMO D7013 ESPRIMO D7013 ESTAR	
Power consumption		
Power consumption note	See white paper Energy Consumption	
Noise emission		
Related Processors for noise	Intel® Core™ i5-13500 processor and 8GB, ODD; Windows 11 (tower position)	
Standard noise emission	According to ISO 7779:2010, ECMA-74	
Standard noise notes / description	A-weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A))	
Standard noise operation mode: CPU 50% load	Bystander; Operator position for SSD M.2 PLATINUM PSU: 3.3 B / 20 dB(A); 21 dB(A) GOLD PSU: 3.2 B / 19 dB(A); 20 dB(A)	
Standard noise operation mode: HDD load	Bystander; Operator position for SSD M.2 PLATINUM PSU: 3.5 B / 22 dB(A); 24 dB(A) GOLD PSU: 3.4 B / 19 dB(A); 20 dB(A)	
Standard noise operation mode: Idle mode	Bystander; Operator position for SSD M.2 PLATINUM PSU: 3.2 B / 19 dB(A); 20 dB(A) GOLD PSU: 3.2 B / 19 dB(A); 20 dB(A)	
Standard noise operation mode: Office applications 2.0	Bystander; Operator position for SSD M.2 PLATINUM PSU: 3.3 B / 19 dB(A); 20 dB(A) GOLD PSU: 3.2 B / 18 dB(A); 20 dB(A)	
Dimensions / Weight / Environmental		
Dimensions (W x D x H)	314 x 296 x 89 mm	
	12.36 x 11.65 x 3.51 inch	
Operating position	horizontal / vertical (optional, feet needed)	
Weight	Min: 5.7kg; 1x mem, 1xSDD Max: 6.0kg; power cord (0.2kg) is not part of min/max	

Dimensions / Weight / Environmental		
Weight (lbs)	approx. 17.64 lbs	
Weight notes	Actual weight may vary depending on configuration	
Operating ambient temperature	10 - 35 °C (50 - 95 °F)	
Operating relative humidity	5 - 85 % (relative humidity)	
Product	ESPRIMO D7013	ESPRIMO D7013 ESTAR
Model	DTG	
Europe	CE	
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL)	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® 8.0 EPEAT® Gold (dedicated regions) in progress TCO Certification in progress
Compliance link	https://sp.ts.fujitsu.com/sites/certificates	
Additional Software		
Additional software (preinstalled)	McAfee® LiveSafe™ (provides award-winning antivirus protection for your PC and much more. 30 days trial pre- installed) Microsoft Office (1 month trial for now Microsoft® Office 265 customers, Pun Microsoft Office)	
Additional software (optional)	Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.) Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) Nero Essentials XL Microsoft® Office Professional 2021 Microsoft® Office Home and Business 2021 (Need to buy license to activate the pre-installed Microsoft Office. Purchase and activation only in the region in which i was acquired.)	
Additional software (notes)	Use of accompanying and/or additional Software is subject to proactive acceptance of the respective License Agreements /EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration.	
Base unit	ESPRIMO D7013	ESPRIMO D7013 ESTAR
Security		
Physical Security	Kensington Lock support Eye for padlock Integrated cabinet lock (optional) Cable Cover (optional; covers and secures the ports and c	ables on rear side)
System and BIOS Security	Embedded security (TPM 2.0) EraseDisk Credential Guard Ready and Device Guard Capable (requires 8 GB or more system RAM and SSD PCIe NVME) Modern Standby (Windows 11 only) and Legacy Standby selectable Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces NIST SP800-147 BIOS Protection supported NIST SP800-155 BIOS Integrity Measurement supported NIST SP800-193 Platform Firmware Resiliency supported	
User Security	User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional Access protection via internal SmartCard reader (optional Access protection via internal SmartCard reader (optional Access protection via internal SmartCard reader (optional	
Security Notes	The properties of the product provide a baseline for prod these properties are not sufficient on their own to protec attempts, data exfiltration and other forms of cyberattack options as available for the respective product. During op responsibility of the respective administrator/end-user of	uct security and therefore end-customer IT security. However, t the product from all existing threats, such as intrusion ss. To customize security settings, please use the configuratior

Manageability	
Manageability technology	Intel® vPro® Essentials (optional)
manageas, teemiology	Intel® vPro® Enterprise (optional)
	Intel AMT 16.0 (optional; depending on processor)
	DeskUpdate Driver management
	PXE 2.1 Boot code
	Wake up from S5 (off mode)
	Intrusion switch (optional)
	WoL (Wake on LAN)
Manageability software	DeskView Client DeskView Instant BIOS Management
DeskView components	BIOS Management incl. Security
	Inventory Management
	Driver Management
	Alarm Management
Supported standards	DMI (Desktop Management Interface)
	SMBIOS (System Management BIOS) PXE (Preboot Execution Environment)
	WMI (Windows Management Instrumentation)
	WBEM (Web Based Enterprise Management)
	CIM (Common Information Model)
Manageability link	https://www.fujitsu.com/global/products/computing/pc/manageability/
Miscellaneous	
	Keyboard on with one key (Fujitsu Keyboards KB521, KB955)
	Keyboard on with two keys (CTRL+CTRL; special Fujitsu USB keyboards required)
	Keyboard on with any key (USB)
	Thermal management
	Extended lifetime
	Internal dust filter (optional)
Packaging information	
Packaging dimension (mm)	499 x 296 x 439 mm
Packaging dimension (inch)	19.65 x 11.65 x 17.28 inch
Max. quantity / pallet	24
Material - Weight (g) Carton	1114 g
Material - Weight (lbs) Carton	2.46 lbs
Material - Weight (g) PE	263 g
Material - Weight (lbs) PE	0.58 lbs
Packaging notes	printed user documentation is bleached in chlorine free process; Bulk packaging for projects (optional)
Warranty	
Warranty period	1 year
Warranty type	Bring-In / Onsite Service (depending on country)
Warranty Terms & Conditions	http://www.fujitsu.com/warranty
Digital bug fixes	Subject to availability and following their generic release for the product, bug fixes and function-preserving patches for
	product-related software (firmware) can be downloaded from the technical support at: https://support.ts.fujitsu.com/
	free of charge by entering the respective product serial number. For application software supplied together with the
	product, please directly refer to the support websites of the respective software manufacturer.
Product Support - the perfect extension	
Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	5 years
Service Weblink	http://www.fujitsu.com/emeia/products/product-support-services/

Recommended Accessories

Keyboard KB955



The KB955 is a very flat keyboard with extra low keys and spill-resistant protection. The elegant design and top-quality construction makes the KB955 the ideal input device for any PC or Notebook user. If you accidently spill some water or coffee onto the keyboard, this special construction helps the liquid to flow away.

S26381-K955-L4** (**: Country specific variation)

More information

Fujitsu products, solutions & services

In addition to Fujitsu Desktop ESPRIMO D7013, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products www.fujitsu.com/global/products/computing/

Software www.fujitsu.com/software/

More information

Learn more about Fujitsu Desktop ESPRIMO D7013, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

www.fujitsu.com/emeia/products/computing/pc/desktops/

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT

Please find further information at http://www.fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see https://www.fujitsu.com/global/about/resources/terms/Copyright 2023 Fujitsu Technology Solutions GmbH

Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering.

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

The overall product has been designed and manufactured for general office use, regular personal use and ordinary industrial use.

Contact

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com 2023-08-04 EM-EN All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see https://www.fujitsu.com/global/about/resources/terms/
Copyright 2023 Fujitsu Technology Solutions GmbH