

# Data Sheet

## FUJITSU PLAN EP E810-XXVDA2 2X 25G SFP28 PCIe

Dual-port 25 Gbit PCIe 4.0

Ethernet cards enable data exchange between all the devices connected in a local network (LAN). A networked IT infrastructure that functions well is of great significance when managing and controlling critical business processes in a company. The wide range of complex information transported across the network relies on fast and reliable data processing by the network cards.



### PLAN EP E810-XXVDA2 2X 25G SFP28 PCIe

The Fujitsu PLAN EP E810-XXVDA2 2X 25G SFP28 Server Adapter is the most flexible and scalable Ethernet adapter for the current demanding data center environments from Intel.

This adapter family addresses the demanding needs of today's generation agile data center by providing unmatched features for both server and network virtualization, flexibility for LAN networks and proven, reliable performance. The PLAN EP E810-XXVDA2 2X 25G SFP28 adapter delivers superior performance with a throughput 100Gb/s, in a PCI Express 4.0 slot.

# Features & Benefits

Main Features	Benefits
Scalable performance <ul style="list-style-type: none"><li>■ Intel® E810-XXVDA2 SFP28 Dual-Port 25G/10GbE Network Adapter</li></ul>	■ Cost- and energy-efficient design delivers superior performance with a theoretical throughput of 100 Gb/s (50 Gb/s Tx; 50Gb/s Rx) bidirectional throughput
Flexible technology options <ul style="list-style-type: none"><li>■ Server Virtualization and VMDq</li></ul>	■ The host-based virtualization technologies supported by Intel VT include VMDq for Emulated Path: Adapter-based Queue sorting enabling efficient hypervisor-based switching
Efficient networking <ul style="list-style-type: none"><li>■ A Complete, Unified Networking Solution; RDMA (iWARP/RoCEv2) for Windows Server</li></ul>	■ Converging data and storage onto one fabric eliminates the need for multiple adapters, cables and switches
Connectivity <ul style="list-style-type: none"><li>■ SR-IOV for Direct Assignment</li></ul>	■ Adapter-based isolation and switching for various virtual station instances enabling optimal CPU usage in virtualized environments

# Technical details

## Technical details

Controller Silicon	Intel® Ethernet Controller E810-XXVAM2			
Controller type	Ethernet Ctrl.			
Connector type	SFP28			
Released drivers list link	<a href="http://support.ts.fujitsu.com/Download/Index.asp">http://support.ts.fujitsu.com/Download/Index.asp</a>			
Number of ports	2			
Data transfer rate(s)	10 Gbit/s / 25 Gbit/s			
Auto Negotiation support	Yes			
Bus interface	PCIe 4.0 x8			
Bus transfer rate	16GT/s			
LEDs	ACTIVITY (blinking) NO ACTIVITY (off) LINK SPEED (green = 25GbE; amber = less than 25GbE; off = no link)			
Network protocol and standards compatibility	IPv4, IPv6 and mixed IPv4/IPv6 network protocols IEEE 802.1p Class of Service IEEE 802.1q VLAN IEEE 802.1Qaz Enhanced Transmission Selection (ETS) IEEE 802.3ae 10Gbit Ethernet IEEE 802.3x Flow Control IEEE 802.1as Timing and Synchronization IEEE 1588 Precision Time Protocol IEEE 802.3az Energy Efficient Ethernet (EEE) SFF 8431 SFP+			
Interrupt Levels	- 2048 interrupts vectors, allocated in a flexible manner to queues and other causes ; - Multiple interrupt moderation scheme; - 20M interrupts/sec			
Virtualization	- Host virtualization via VMDQ and SR-IOV - Up to 256 SR-IOV Virtual Functions - Stateless offloads for tunneled packets (network virtualization support) - Malicious VF protection - Virtual machine load balancing (VMLB) - Advanced packet filtering - VLAN support with VLAN tag insertion, stripping and packet filtering for up to 4096 VLAN tags - VxLAN, GENEVE, NVGRE, MPLS, VxLAN-GPE with Network Service Headers (NSH) - Intel® Ethernet Adaptive Virtual Function drivers			
Teaming	Depends on OS			
Remote boot support	PXE			
iSCSI support	Yes			
Offloading	- TCP Stateless Offloads (include checksum, TSO, VMDq and RSS) - TX/RX IP, SCTP, TCP & UDP checksum offload (IPv4, IPv6) capabilities - iSCSI Host Initiator - Flow Classification (Trafficking data flows across multiple consumers and connections)			
Data transfer rate up to	25 Gbit/s			
Order code	Product Name	Height of bracket	Number of ports	Related product
PYBLA402L	PLAN EP E810-XXVDA2 2X 25G SFP28 PCIe LP	Low Profile (LP)	2	PRIMERGY Server
PYBLA402	PLAN EP E810-XXVDA2 2X 25G SFP28 PCIe	Full Height (FH)	2	PRIMERGY Server
PY-LA402	PLAN EP E810-XXVDA2 2X 25G SFP28 PCIe	Full Height / Low Profile	2	PRIMERGY Server
Supported Interface Modules / Cables				
Order code	Application	Type / mode	Connector / cable Length	
PYBSFPS56	Ethernet 25 Gbit/s	QSFP28 / MMF (SWL)	up to 100m	
PY-SFPS56	Ethernet 25 Gbit/s	QSFP28 / MMF (SWL)	up to 100m	
Environment				
Power consumption	typ. 12.1 W, max. 13.7 W			

Environment

Power consumption

Temperature (operating)	0 - 55 °C
Storage temperature	-40 - 70 °C

Compliance

Compliance notes	According to the corresponding system
Compliance link	<a href="https://sp.ts.fujitsu.com/sites/certificates">https://sp.ts.fujitsu.com/sites/certificates</a>

# More information

Fujitsu products, solutions & services

In addition to Fujitsu with PLAN EP E810-XXVDA2 2X 25G SFP28 PCIe, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio  
Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products  
[www.fujitsu.com/global/products/computing/](http://www.fujitsu.com/global/products/computing/)

Software  
[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

More information

Learn more about Fujitsu PLAN EP E810-XXVDA2 2X 25G SFP28 PCIe, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. [www.fujitsu.com/primergy](http://www.fujitsu.com/primergy)

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <https://www.fujitsu.com/global/about/resources/terms/> Copyright 2024 Fujitsu LIMITED

Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering. The product was developed for normal business use. Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.