

# Data Sheet FUJITSU PLAN EP X710-T4 4x 10GBase-T Ethernet Network Adapter

X710-T4 4x 10GBase-T PCle v3 x8 adapter

Ethernet cards enable data exchange between all the devices connected in a local network (LAN). A networked IT infrastructure that functions well is of great significance when managing and controlling critical business processes in a company. The wide range of complex information transported across the network relies on fast and reliable data processing by the network cards.

that most customers require for a smooth transition and easy migration to 10 GbE.

10GBASE-T uses the copper twisted-pair cables that are very familiar to IT professionals today.



# PLAN EP X710-T4 4x 10GBase-T Ethernet Network Adapter

10 GbE for the Broad Market. Intel(R) Ethernet 700 Series Network Adapters are the foundation for server connectivity, providing broad ineroperability, critical performance optimizations, and increased agility for Telecommunications, Cloud, and Enterprise IT network solutions. The Intel Ethernet Network Adapter X710-T4 is the newest innovation in Intel's leadership to drive 10 GbE into the broad server market, and the easiest and most versatile 10GbE interface that can deployed anywhere in the data center.

Simplify the Transition to 10GbE. With 10GBASE-T, migration to 10GbE is dramatically simplified with backward compatibility for your existing GbE network infrastructure. Install a Fujitsu PLAN EP X710-T4 Quad Port PCle adapter into a server and the autonegotiation between 1 GbE and 10 GbE provides the necessary backwards compatibility

#### **Main Features** Benefits Scalable performance ■ Intel® Ethernet Network Adapter X710-T4 ■ Enables higher bandwidth and throughput from standard and lowprofile PCIe slots and servers Flexible OS support ■ Support for most Network Operating Systems ■ Enables widespread deployment Efficient networking ■ Network Virtualization offloads including VXLAN, GENEVE, NVGRE, ■ Enhanced Network Virtualization Overlays MLPS, and VLAN-GPE; network traffic can be distributed across CPU cores, increasing network throughput Connectivity ■ RJ45 Connections over CAT 6A Cabling ■ Ensures compatibility with cable length up to 100 meters. Backwards compatible with existing 100BASE-T and 1000BASE-T networks

Page 1 / 4 www.fujitsu.com/primergy

## Technical details

Technical det	

lechnical details				
Controller Silicon	Intel® Ethernet Controller XL710			
Controller type	Ethernet Ctrl.			
Connector type	RJ45			
Released drivers list link	http://support.ts.fujitsu.com/Downlo	ad/Index.asp		
Number of ports	4			
Number of Connectors	4			
Number of external ports	4			
Data transfer rate(s)	100 MBit/s; 1 Gbit/s; 10 Gbit/s			
Auto Negotiation support	Yes			
Bus interface	PCIe 3.0 x8			
Bus transfer rate	8GT/s			
Network protocol and standards compatibility	IEEE 802.1p IEEE 802.1q VLAN IEEE 802.3ad LACP IEEE 802.3 2005 flow control support			
HW Virtualization	PCI-SIG SR-IOV with up to 128 virtual	functions per device		
Interrupt Levels	INTA; MSI; MSI-X			
WoL	No			
Virtualization	VMDq (Virtual Machine Device Queues) up to 256 maximum VMDq VMs supported PCI-SIG SR-IOV up to 128 per device. The physical configuration of each port is divided into multiple virtual ports VMLB (Virtual Maschine Load Balancing) provides traffic load balancing across VMs bound to the team interface			
Teaming	Provided by the OS			
Remote boot support	iSCSI ; PXE			
iSCSI support	Yes			
Offloading	Tx/Rx IP, SCTP, TCP and UDP checksum offloading (IPv4 & IPv6). Benefit: lower processor usage. Checksum and segmentation capability to extend to new standard packet type			
Data transfer rate up to	10 Gbit/s			
Order code	Product Name	Height of bracket	Number of ports	Related product
MC-0JXF11	PLAN EP X710-T4	Low Profile (LP)	4	PRIMEQUEST Server
MCX0JXF11	PLAN EP X710-T4	Full Height / Low Profile	4	PRIMEQUEST Server
S26361-F3948-E204	PLAN EP X710-T4	Low Profile (LP)	4	PRIMERGY Server
S26361-F3948-E4	PLAN EP X710-T4	Full Height (FH)	4	PRIMERGY Server
S26361-F3948-L504	PLAN EP X710-T4	Full Height / Low Profile	4	PRIMERGY Server
Supported Interface Modules / Cables				

### Supported Interface Modules / Cables

Description optional cable

10GBASE-T

- 100m on Cat 6A or Cat 7
- 55m on Cat 6 (compliant to TSB-155)

1000BASE-T

- 100m on Cat 5e, Cat 6, Cat 6A or CAT 7

100BASE-T

- 100m on Cat 5e, Cat 6, Cat 6A or CAT 7

Envir	ัดทเ	mei	٦t

Power consumption	100 Mbps: typical 9.2W, maximum 14.9W 1GbE: typical 12.0W, maximum 18.1W 10GbE: typical 24.7W, maximum 28.9 W
Compliance	
Europe	CE
USA/Canada	FCC Class B UL
Japan	VCCI

Page 2 / 4 www.fujitsu.com/primergy

Compliance	
South Korea	KCC
Australia/New Zealand	C-Tick
Taiwan	BSMI
Compliance notes	According to the corresponding system
Compliance link	https://sp.ts.fujitsu.com/sites/certificates

Page 3 / 4 www.fujitsu.com/primergy

### More information

#### Fujitsu products, solutions & services

In addition to Fujitsu with PLAN EP X710-T4 4x 10GBase-T Ethernet Network Adapter, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

#### Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products www.fujitsu.com/global/products/ computing/

Software www.fujitsu.com/software/

#### More information

Learn more about Fujitsu PLAN EP X710-T4 4x 10GBase-T Ethernet Network Adapter, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. www.fujitsu.com/primergy

#### Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT

Please find further information at http://www.fujitsu.com/global/about/environment



### Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see https://www.fujitsu.com/global/about/resources/terms/Copyright 2024 Fujitsu LIMITED

#### Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering. The product was developed for normal business use.

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

#### Contact

Fujitsu Limited Website: www.fujitsu.com/primergy 2024-05-06 WW-EN All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see https://www.fujitsu.com/global/about/resources/terms/
Copyright 2024 Fujitsu LIMITED