

Data Sheet

Fujitsu Thin Client FUTRO S5011

Ultra-compact and Powerful Thin Client

The FUTRO S5011 is an ultra-compact and powerful Thin Client device for companies that need endpoints for their VDI and cloud client computing scenarios. The FUTRO S5011 has an optimal mix of industry leading OS, Thin Client device management consoles and flexible hardware options helping you provide secure computing and full productivity choices for your employees.

Improved performance with advanced technology

Ultimate performance to meet the business challenges of future computing

- AMD Ryzen[™] embedded R1305G processors
- Fast NVM storage technology
- Fanless, zero noise Thin Client

eLux RP 6 Thin Client OS and Scout Enterprise Management Suite® 15
Enables upfront cost savings and keeps your IT infrastructure secure, up-to-date with continuous security patch releases

 Unicon offers a flexible licensing model that offers the eLux OS and Scout Enterprise Management Suite including Cloud Gateway with long term support for the latest updates

Enterprise-grade security

Enables you to provide a secure end-point device that helps prevent unauthorized access to sensitive enterprise data

 Centralized administration and granular access controls coupled with built-in BIOS security, Write Filter Protection and Kensington lock support

Ultra-compact design with improved connectivity

Be flexible and stay productive in a hyper-connected world

- Fully equipped Thin Client with a volume of only ~0.86 liters
- USB Speed up to 10 Gbps
- 5 USB ports with 1 USB Type-C port

Full productivity

The PC which will transform your workplace for the next gen needs

UC&C ready with multi-monitor support for up to two displays and ideal mix of modern (Type-C) and legacy interfaces













Technical details Components

| Storage notes | Important Notice for M.2 Module Use: Predefined by NAND-Flash-Technology the device only supports a defined maximum number of Terabytes written. Any and all warranty for such devices is limited to this maximum Terabytes written. Please notice the section |
|--|---|
| | "restricted warranty" in our warranty book. |
| | Fujitsu therefore strongly recommends to activate the write filter of the M.2 module once the configuration is |
| | finished. This activation ensures the durability of the flash module and is also mandatory to ensure a highest level |
| | of IT security (e.g. against virus attacks). In case of a need to enable further write cycles the write filter can then be |
| | deactivated again at any time. |
| | *Terabytes written (TBW) calculated based on JESD-219A SSD Client workload One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. |
| | One digabyte equals one billion bytes, when relenting to hard disk drive capacity. |
| Base unit | FUTRO S5011 |
| Operating system and software (Lin | nux) |
| Operating system | eLux® RP |
| Notes | eLux® is a hardware-independent operating system for cloud computing environments. eLux ensures hardware |
| | independence and migration ability. An existing license can simply be transferred via Scout Enterprise whenever the hardware is upgraded. New updates and upgrades are always built modular – only the changed parts (delta) |
| | of the software are transferred to the device and implemented into the existing installation. Software updates and |
| | upgrades are available around the clock at myelux.com. |
| Functions | eLux® RP 6 |
| | Citrix Receiver |
| | VMware® Horizon Client |
| | Updates and optional software packages are available at www.myelux.com |
| Manageability | Scout Enterprise, flash memory management, embedded operating system update and system monitoring, |
| | managing devices by location, group or user, individual operating system composition with ELIAS (eLux and Scout Enterprise Management Suite license required) |
| Operating system and software (Wi | indows 10 IoT) |
| Operating system | Windows® 10 IoT Enterprise 2021 LTSC |
| Notes | Windows 10 Support: After the end of the product life Fujitsu will continue to test and support all upcoming Window 10 releases for a period of maximum 5 years – depending on the available extension of hardware services through Fujitsu Warranty top ups. For details please see "Fujitsu Service Statement for Windows 10 Semi-Annual-Channel |
| | Support" at http://support.ts.fujitsu.com. |
| Functions | Internet Explorer |
| | Citrix Receiver |
| | VMware® Horizon Client |
| Security software | |
| Additional software (notes) | Use of accompanying and/or additional Software is subject to proactive acceptance of the respective License |
| | Agreements /EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant |
| | Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration. |
| Mainboard | |
| | |
| Mainboard type | subscription which – depending on the Software - may be subject to separate remuneration. |
| Mainboard type Processor | subscription which – depending on the Software - may be subject to separate remuneration. D3944-B1 |
| Mainboard type Processor Memory slots | subscription which – depending on the Software - may be subject to separate remuneration. D3944-B1 AMD Ryzen™ Embedded R1000 Series R1305G (Dual Core, 1.5 GHz, up to 2.8 GHz, AMD Radeon™ Vega 3 Graphics) (,) |
| Mainboard type Processor Memory slots Supported capacity RAM (max.) | subscription which – depending on the Software - may be subject to separate remuneration. D3944-B1 AMD Ryzen™ Embedded R1000 Series R1305G (Dual Core, 1.5 GHz, up to 2.8 GHz, AMD Radeon™ Vega 3 Graphics) (,) 1 SO DIMM (DDR4, 2400 MHz) |
| Mainboard type Processor Memory slots Supported capacity RAM (max.) LAN | subscription which – depending on the Software - may be subject to separate remuneration. D3944-B1 AMD Ryzen™ Embedded R1000 Series R1305G (Dual Core, 1.5 GHz, up to 2.8 GHz, AMD Radeon™ Vega 3 Graphics) (,) 1 SO DIMM (DDR4, 2400 MHz) 8 GB 10/100/1,000 MBit/s Realtek RTL8111H BIOS Flash EPROM update by software Recovery BIOS |
| Mainboard type Processor Memory slots Supported capacity RAM (max.) LAN BIOS features | subscription which – depending on the Software - may be subject to separate remuneration. D3944-B1 AMD Ryzen™ Embedded R1000 Series R1305G (Dual Core, 1.5 GHz, up to 2.8 GHz, AMD Radeon™ Vega 3 Graphics) (,) 1 SO DIMM (DDR4, 2400 MHz) 8 GB 10/100/1,000 MBit/s Realtek RTL8111H BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI) |
| Mainboard type Processor Memory slots Supported capacity RAM (max.) LAN BIOS features Audio type | subscription which – depending on the Software - may be subject to separate remuneration. D3944-B1 AMD Ryzen™ Embedded R1000 Series R1305G (Dual Core, 1.5 GHz, up to 2.8 GHz, AMD Radeon™ Vega 3 Graphics) (,) 1 SO DIMM (DDR4, 2400 MHz) 8 GB 10/100/1,000 MBit/s Realtek RTL8111H BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI) On board |
| Mainboard type Processor Memory slots Supported capacity RAM (max.) LAN BIOS features Audio type | subscription which – depending on the Software - may be subject to separate remuneration. D3944-B1 AMD Ryzen™ Embedded R1000 Series R1305G (Dual Core, 1.5 GHz, up to 2.8 GHz, AMD Radeon™ Vega 3 Graphics) (,) 1 SO DIMM (DDR4, 2400 MHz) 8 GB 10/100/1,000 MBit/s Realtek RTL8111H BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI) |
| Mainboard Mainboard type Processor Memory slots Supported capacity RAM (max.) LAN BIOS features Audio type Audio codec Interfaces | subscription which – depending on the Software - may be subject to separate remuneration. D3944-B1 AMD Ryzen™ Embedded R1000 Series R1305G (Dual Core, 1.5 GHz, up to 2.8 GHz, AMD Radeon™ Vega 3 Graphics) (,) 1 SO DIMM (DDR4, 2400 MHz) 8 GB 10/100/1,000 MBit/s Realtek RTL8111H BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI) On board |

Page 2 / 6

| Interfaces | |
|-------------------------------------|--|
| Front audio: headphone | 1 |
| USB 2.0 total | 3 |
| USB 3.2 Gen2 (10 Gbps) total | 2 |
| USB front | 1x USB 3.2 Gen 2 1x USB 3.2 Gen 2 Type-C |
| USB rear | 3x USB 2.0 |
| USB internal | 1 pin header |
| DisplayPort | 2 (DisplayPort 1.4) |
| Ethernet (RJ-45) | 1 |
| Kensington Lock support | 1 |
| Graphics on board | |
| Graphics brand name | AMD Radeon™ Vega 3 Graphics |
| Graphics color depth | 32 bit colors |
| TFT resolution (DisplayPort) | up to 4,096 x 2,160 @ 60 Hz |
| Graphics features | DirectX® 12 |
| • | OpenGL * 4.6 |
| | Vulkan™ |
| | Open CL® 2.2 |
| Graphics notes | Graphics resolution and performance depends on operating system and infrastructure environment. It is strongly recommended to test and validate the target use case. |
| Electrical values | |
| Power consumption long idle | 6.10 W |
| Power consumption sleep mode power | 1.59 W (WoL enabled) |
| Power consumption off mode power | 0.26 W (WoL disabled) |
| Rated voltage range | 100 V - 240 V (AC Input) |
| Rated frequency range | 50 Hz - 60 Hz |
| Operating voltage range | 100 V - 240 V (AC Input) |
| Operating line frequency range | 50 Hz - 60 Hz |
| Dimensions / Weight / Environmental | |
| Dimension with stand (W x D x H) | 68 x 165 x 156 mm |
| Dimensions (W x D x H) | 36 x 165 x 147 mm |
| Operating position | Vertical / horizontal |
| Weight | min: 605 g (1 x memory, 1x SSD, w/o AC-Adapter) max: 613 g (full expansion, w/o AC-Adapter) AC-Adapter + power cord: 277 g |
| Weight notes | Actual weight may vary depending on configuration |
| Operating ambient temperature | 10 - 35 °C |
| Operating relative humidity | 5 - 85 % (relative humidity) |
| Compliance | |
| Product | FUTRO S5011 |
| Model | TCS6 |
| Germany | GS |
| Global | RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) |
| Compliance link | https://sp.ts.fujitsu.com/sites/certificates |
| Security | |
| Physical Security | Kensington Lock support |
| System and BIOS Security | Trusted Platform Module (TPM 2.0), optional without TPM User and supervisor BIOS password |
| | |

Page 3 / 6 www.fujitsu.com/emeia/FUTRO

| Security | |
|---|---|
| Security Notes | The properties of the product provide a baseline for product security and therefore end-customer IT security. However, these properties are not sufficient on their own to protect the product from all existing threats, such as intrusion attempts, data exfiltration and other forms of cyberattacks. To customize security settings, please use the configuration options as available for the respective product. During operation, the IT security of this product is within the responsibility of the respective administrator/end-user of the product. Please note, that Fujitsu as a manufacturer does not make any policy prescriptions or advocacy statements regarding IT security best practices and/or general product operation. |
| Packaging information | |
| Packaging dimension (mm) | 395 x 197 x 288 mm |
| Packaging dimension (inch) | 15.55 x 7.76 x 11.34 inch |
| Max. quantity / pallet | 72 |
| Material - Weight (g) Carton | 698 g |
| Material - Weight (lbs) Carton | 1.54 lbs |
| Material - Weight (g) EPS / PS | 0 g |
| Material - Weight (lbs) EPS / PS | 0 lbs |
| Material - Weight (g) PE | 20 g |
| Material - Weight (lbs) PE | 0.04 lbs |
| Packaging notes | If keyboard is included in packaging, dimension is increasing to: $497 \times 206 \times 293$ mm and material weight of carton will increase to 901 g |
| Warranty | |
| Warranty period | 2 years (depending on country) |
| Warranty type | Bring-In / Onsite Service (for countries within region EMEIA, for all other countries depending on local regulations) |
| Warranty Terms & Conditions | http://www.fujitsu.com/warranty |
| Digital bug fixes | Subject to availability and following their generic release for the product, bug fixes and function-preserving patches for product-related software (firmware) can be downloaded from the technical support at: https://support.ts.fujitsu.com/free of charge by entering the respective product serial number. For application software supplied together with the product, please directly refer to the support websites of the respective software manufacturer. |
| Product Support - the perfect extension | |
| Recommended Service | 9x5, Onsite Response Time: Next Business Day |
| Spare Parts availability | at least 5 years after shipment, for details see https://support.ts.fujitsu.com/ |
| Service Weblink | http://www.fujitsu.com/emeia/products/product-support-services/ |
| | |

Recommended Accessories

VESA Mounting Kit for FUTRO S7011, S5011



Mounting Kit incl. cable cover for displays or mounting solutions with 10x10 VESA mount points

Order Code: FPCSK737GP

Mounting Kit for Height Adjustable Fujitsu Displays - up to 10th Gen. Display



The Fujitsu Mounting Kit for Height Adjustable Fujitsu Displays has been specifically designed for use with ESPRIMO Q/G Mini PCs, FUTRO Thin Clients and Fujitsu Displays. With this solution you can save space on the desk, reduce clutter on desk and realize a clean desk working environment.

Order Code: FPCSK740GP

Mouse M520 black



The Fujitsu Accessory Mouse M520 black is an essential input device for PCs that works on nearly every surface and follows your hand movements smoothly and precisely. It features two buttons and a scroll wheel which also can be used as third button.

Order Code: S26381-K467-L100

Page 4 / 6

Mouse M520 grey



The Fujitsu Accessory Mouse M520 grey is an essential input device for PCs that works on nearly every surface and follows your hand movements s26381-K467-L101 smoothly and precisely. It features two buttons and a scroll wheel which also can be used as third button.

Order Code:

Page 5 / 6 www.fujitsu.com/emeia/FUTRO

More information

Fujitsu products, solutions & services

In addition to Fujitsu Thin Client FUTRO S5011, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products www.fujitsu.com/global/products/computing/

Software www.fujitsu.com/software/

More information

Learn more about Fujitsu Thin Client FUTRO S5011, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/emeia/FUTRO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT

Please find further information at http://www.fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see https://www.fujitsu.com/global/about/resources/terms/Copyright 2024 Fujitsu Technology Solutions GmbH

Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering.

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

The overall product has been designed and manufactured for general office use, regular personal use and ordinary industrial use.

Contact

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com 2024-04-06 EM-EN All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see https://www.fujitsu.com/global/about/resources/terms/
Copyright 2024 Fujitsu Technology Solutions GmbH