# FUJITSU

## Data Sheet Fujitsu Thin Client FUTRO S7011 ESTAR

### Ultra-compact and powerful Thin Client

The FUTRO S7011 is an ultra-compact and powerful Thin Client device for companies that need flexible end-points with an optimal mix of industry leading OS, Thin Client device management consoles and flexible hardware options helping you provide secure client cloud computing and full productivity choices for your employees

Improved performance with advanced technology

Ultimate performance to meet the business challenges of future computing

- AMD Ryzen<sup>™</sup> embedded R1505G processors & fast NVM Storage technology
- Fanless, zero noise Thin Client with dual channel memory support

eLux RP 6 Thin Client OS and Scout Enterprise Management Suite® 15 Enables upfront cost savings and keeps your IT infrastructure secure, up-to-date with continuous security patch releases

Unicon offers a flexible licensing model that offers the eLux OS and Scout Enterprise Management Suite including Cloud Gateway with long term support for the latest updates

### Enterprise-grade security

Enables you to provide a secure end-point device that helps prevent unauthorized access to sensitive enterprise data

Centralized administration and granular access controls coupled with built-in BIOS Security, Write Filter Protection and Kensington lock support

### Ultra-compact design with improved connectivity

- Be flexible and stay productive in a hyper-connected world
- Fully equipped Thin Client with a volume of only ~0.86 liters
- USB speed up to 10 Gbps
- Up to 7 USB Ports with 3 USB Type-C ports, variety of different display connectors

### Full productivity

The PC which will transform your workplace for the next gen needs

- UC&C ready with multi-monitor support for up to three displays and ideal mix of modern (Type-C) and legacy interfaces
- Run the system with just one single USB-C cable for a clean desk













### Technical details Components

Storage notes	Important Notice for M.2 Module Use: Predefined by NAND-Flash-Technology the device only supports a defined maximum number of Terabytes written.		
	Any and all warranty for such devices is limited to this maximum Terabytes written. Please notice the section "restricted warranty" in our warranty book. Fujitsu therefore strongly recommends to activate the write filter of the M.2 module once the configuration is		
	finished. This activation ensures the durability of the flash module and is also mandatory to ensure a highest level		
	of IT security (e.g. against virus attacks). In case of a need to enable further write cycles the write filter can then be		
	deactivated again at any time.		
	*Terabytes written (TBW) calculated based on JESD-219A SSD Client workload One Gigabyte equals one billion bytes, when referring to hard disk drive capacity.		
	One digabyte equals one billion bytes, when relenning to hard disk drive capacity.		
Base unit	FUTRO S7011 ESTAR		
Operating system and software (Linux)			
Operating system	eLux® RP		
Notes	eLux <sup>®</sup> is a hardware-independent operating system for cloud computing environments. eLux ensures hardware independence and migration ability. An existing license can simply be transferred via Scout Enterprise whenever the hardware is upgraded. New updates and upgrades are always built modular – only the changed parts (delta)		
	of the software are transferred to the device and implemented into the existing installation. Software updates and upgrades are available around the clock at myelux.com.		
unctions	eLux® RP 6		
	Citrix Receiver		
	VMware® Horizon Client		
	Updates and optional software packages are available at www.myelux.com		
<b>J</b> anageability	Scout Enterprise, flash memory management, embedded operating system update and system monitoring, managing devices by location, group or user, individual operating system composition with ELIAS (eLux and Scout Enterprise Management Suite license required)		
Operating system and software (Window			
Dperating system	Windows® 10 IoT Enterprise 2021 LTSC		
lotes	Windows 10 Support: After the end of the product life Fujitsu will continue to test and support all upcoming Wind 10 releases for a period of maximum 5 years – depending on the available extension of hardware services throug Fujitsu Warranty top ups. For details please see "Fujitsu Service Statement for Windows 10 Semi-Annual-Channel		
Functions	Support" at http://support.ts.fujitsu.com.		
unctions	Internet Explorer Citrix Receiver		
	VMware® Horizon Client		
Security software			
•	Use of accompanying and/or additional Software is subject to proactive acceptance of the respective License Agreements /EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration.		
dditional software (notes)	Use of accompanying and/or additional Software is subject to proactive acceptance of the respective License Agreements /EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support		
dditional software (notes) Aainboard	Use of accompanying and/or additional Software is subject to proactive acceptance of the respective License Agreements /EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support		
dditional software (notes) Aainboard Aainboard type	Use of accompanying and/or additional Software is subject to proactive acceptance of the respective License Agreements /EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration. D3944-A1		
dditional software (notes) <mark>Iainboard</mark> Iainboard type rocessor	Use of accompanying and/or additional Software is subject to proactive acceptance of the respective License Agreements /EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration. D3944-A1		
dditional software (notes) Aainboard Aainboard type rocessor Aemory slots	Use of accompanying and/or additional Software is subject to proactive acceptance of the respective License Agreements /EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration. D3944-A1 AMD Ryzen <sup>™</sup> Embedded R1000 Series R1505G (Dual Core, 2.4 GHz, up to 3.3 GHz, AMD Radeon <sup>™</sup> Vega 3 Graphics) (,		
Aditional software (notes) Aainboard Aainboard type rocessor Aemory slots upported capacity RAM (max.)	Use of accompanying and/or additional Software is subject to proactive acceptance of the respective License Agreements /EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration. D3944-A1 AMD Ryzen™ Embedded R1000 Series R1505G (Dual Core, 2.4 GHz, up to 3.3 GHz, AMD Radeon™ Vega 3 Graphics) (, 2 SO DIMM (DDR4, 2400 MHz)		
Additional software (notes) Aainboard Aainboard type Processor Aemory slots Supported capacity RAM (max.) Aemory notes	Use of accompanying and/or additional Software is subject to proactive acceptance of the respective License Agreements /EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration. D3944-A1 AMD Ryzen™ Embedded R1000 Series R1505G (Dual Core, 2.4 GHz, up to 3.3 GHz, AMD Radeon™ Vega 3 Graphics) (, 2 SO DIMM (DDR4, 2400 MHz) 16 GB		
Security software Additional software (notes) Mainboard Mainboard type Processor Memory slots Supported capacity RAM (max.) Memory notes AN BIOS features	Use of accompanying and/or additional Software is subject to proactive acceptance of the respective License Agreements /EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration. D3944-A1 AMD Ryzen™ Embedded R1000 Series R1505G (Dual Core, 2.4 GHz, up to 3.3 GHz, AMD Radeon™ Vega 3 Graphics) (, 2 SO DIMM (DDR4, 2400 MHz) 16 GB For dual channel performance and full graphics support, 2 memory modules have to be ordered Built-in 10/100/1,000 MBit/s Realtek RTL8111H BIOS Flash EPROM update by software Recovery BIOS		
Additional software (notes) Mainboard Mainboard type Processor Memory slots Supported capacity RAM (max.) Memory notes LAN	Use of accompanying and/or additional Software is subject to proactive acceptance of the respective License Agreements /EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration. D3944-A1 AMD Ryzen™ Embedded R1000 Series R1505G (Dual Core, 2.4 GHz, up to 3.3 GHz, AMD Radeon™ Vega 3 Graphics) (, 2 SO DIMM (DDR4, 2400 MHz) 16 GB For dual channel performance and full graphics support, 2 memory modules have to be ordered Built-in 10/100/1,000 MBit/s Realtek RTL8111H BIOS Flash EPROM update by software		

Compliance link	https://sp.ts.fujitsu.com/sites/certificates			
	WEEE (Waste electrical and electronic equipment) ENERGY STAR® 8.0 TCO Certified 9.0 EPEAT® Silver (dedicated regions)			
Germany Global	GS RoHS (Restriction of hazardous substances)			
Model	TCS6			
Product	FUTRO S7011			
Compliance				
	5 - 85 % (relative humidity)			
Operating ambient temperature	10-35 °C			
Veight notes Operating ambient temperature	Actual weight may vary depending on configuration			
	max: 664 g (full expansion, w/o AC-Adapter) AC-Adapter + power cord: 277 g			
Veight	min: 624 g (1 x memory, 1x SSD, w/o AC-Adapter)			
perating position	Vertical / horizontal			
Dimensions (W x D x H)	36 x 165 x 147 mm			
Dimension with stand $(W \times D \times H)$	68 x 165 x 156 mm			
Dimensions / Weight / Environmental				
Dperating line frequency range	50 Hz - 60 Hz			
Derating voltage range	100 V - 240 V (AC Input)			
lated frequency range	50 Hz - 60 Hz			
Rated voltage range	100 V - 240 V (AC Input)			
ower consumption off mode power	0.27 W (WoL disabled)			
ower consumption sleep mode power	1.62W (WoL disabled)			
ower consumption long idle	5.99 W			
lectrical values	It is strongly recommended to test and validate the target use case.			
raphics notes	Graphics resolution and performance depends on operating system and infrastructure environment.			
	OpenGL® 4.6 Vulkan™ Open CL® 2.2			
Graphics features	DirectX® 12			
FT resolution (DisplayPort)	up to 4,096 x 2,160 @ 60 Hz			
Graphics color depth	32 bit colors			
Graphics brand name	AMD Radeon™ Vega 3 Graphics			
Graphics on board				
Kensington Lock support	1			
nterface Module notes	*only one "optional" interface can be configured at the same time.			
Ethernet (RJ-45)	1 + 1 (optional* 2.5GB LAN)			
HDMI	1 (optional* Supports 4K@60Hz as specified in HDMI <sup>™</sup> 2.1)			
Serial (RS-232)	1 (optional) + 1 (optional*)			
DisplayPort	2 (DisplayPort 1.4) + 1 (optional*)			
JSB internal	3x USB 2.0 1 pin header			
ISB rear	1x USB 3.2 Gen 2 Type-C   1x USB 3.2 Gen 2 Type-C + 1 (optional*, supports DisplayPort and power delivery sink support e.g. from a display)			
JSB front	1x USB 3.2 Gen 2			
SB 3.2 Gen2 (10 Gbps) total	3			
JSB 2.0 total	3			
ront audio: headphone	1			
DC-in				

Security			
Physical Security	Kensington Lock support		
System and BIOS Security	Trusted Platform Module (TPM 2.0), optional without TPM User and supervisor BIOS password		
Security Notes	The properties of the product provide a baseline for product security and therefore end-customer IT security. How these properties are not sufficient on their own to protect the product from all existing threats, such as intrusion attempts, data exfiltration and other forms of cyberattacks. To customize security settings, please use the configu options as available for the respective product. During operation, the IT security of this product is within the responsibility of the respective administrator/end-user of the product. Please note, that Fujitsu as a manufacturer not make any policy prescriptions or advocacy statements regarding IT security best practices and/or general procoperation.		
Packaging information			
Packaging dimension (mm)	395 x 197 x 288 mm		
Packaging dimension (inch)	15.55 x 7.76 x 11.34 inch		
Max. quantity / pallet	72		
Material - Weight (g) Carton	698 g		
Material - Weight (lbs) Carton	1.54 lbs		
Material - Weight (g) EPS / PS	0 g		
Material - Weight (lbs) EPS / PS	0 lbs		
Material - Weight (g) PE	20 g		
Material - Weight (lbs) PE	0.04 lbs		
Packaging notes	including keyboard: dimension: 497 x 206 x 293mm weight carton: 901g		
Warranty			
Warranty period	2 years (depending on country)		
Warranty type	Bring-In / Onsite Service (for countries within region EMEIA, for all other countries depending on local regulations)		
Warranty Terms & Conditions	http://www.fujitsu.com/warranty		
Digital bug fixes	Subject to availability and following their generic release for the product, bug fixes and function-preserving patch product-related software (firmware) can be downloaded from the technical support at: https://support.ts.fujitsu.c free of charge by entering the respective product serial number. For application software supplied together with the product, please directly refer to the support websites of the respective software manufacturer.		
Product Support - the perfect extension			
Recommended Service	9x5, Onsite Response Time: Next Business Day		
Spare Parts availability	at least 5 years after shipment, for details see https://support.ts.fujitsu.com/		
Service Weblink	http://www.fujitsu.com/emeia/products/product-support-services/		

### **Recommended Accessories**

USB-C Lock Cable (20 pcs)



VESA Mounting Kit for FUTRO S7011, S5011



The Fujitsu USB-C lock cable with a dual screw locking ensures a firm Order Code: connection to dedicated devices of Fujitsu Displays or FUTRO Thin Clients. \$26391-F6058-L420

Mounting Kit incl. cable cover for displays or mounting solutions with 10x10 VESA mount points

Order Code: FPCSK737GP

Mounting Kit for Height Adjustable Fujitsu Displays - up to 10th Gen. Display	The Fujitsu Mounting Kit for Height Adjustable Fujitsu Displays has been specifically designed for use with ESPRIMO Q/G Mini PCs, FUTRO Thin Clients and Fujitsu Displays. With this solution you can save space on the desk, reduce clutter on desk and realize a clean desk working environment.	Order Code: FPCSK740GP
Mouse M520 black	The Fujitsu Accessory Mouse M520 black is an essential input device for PCs that works on nearly every surface and follows your hand movements smoothly and precisely. It features two buttons and a scroll wheel which also can be used as third button.	Order Code: S26381-K467-L100
Mouse M520 grey	The Fujitsu Accessory Mouse M520 grey is an essential input device for PCs that works on nearly every surface and follows your hand movements smoothly and precisely. It features two buttons and a scroll wheel which also can be used as third button.	Order Code: S26381-K467-L101

### More information

#### Fujitsu products, solutions & services

In addition to Fujitsu Thin Client FUTRO S7011 ESTAR, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

#### Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products www.fujitsu.com/global/products/ computing/

Software www.fujitsu.com/software/

#### More information

Learn more about Fujitsu Thin Client FUTRO S7011 ESTAR, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

www.fujitsu.com/emeia/FUTRO

### Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at http://www. fujitsu.com/global/about/environment



### Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see https://www.fujitsu.com/ global/about/resources/terms/ Copyright 2024 Fujitsu Technology Solutions GmbH

### Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering.

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

The overall product has been designed and manufactured for general office use, regular personal use and ordinary industrial use.

Contact

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com 2024-04-06 EM-EN All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see https://www.fujitsu.com/global/about/resources/terms/ Copyright 2024 Fujitsu Technology Solutions GmbH