

Data Sheet

Fujitsu PRAID EP580i


RAID Controller SAS 12Gbit/s 8GB cache based on Broadcom MegaRAID® for internal storage devices

The RAID architecture (Redundant Array of Independent Disks) combines multiple storage devices, including hard drives and NVMe devices, into a single logical unit. Redundancy data is generated from data segments (barring RAID 0) and distributed across the devices. Consequently, operating systems interact with this collective array rather than the individual devices. The core purpose of RAID is to enhance data availability, reducing potential disruptions from storage devices failures. The effectiveness of a RAID setup largely depends on the RAID controller in use. Choose Fujitsu RAID controllers for a blend of modern technology and proven experience, providing the data protection that businesses need today.

PRAID EP580i

The Fujitsu RAID Controller PRAID EP580i with 8GB cache and 16x12Gbit/s SAS ports improves performance for storage intensive workloads such as databases and sets new speed and data security standards for internal storage drives. The new PRAID EP580i supports up to 16 SAS/SATA drives, up to 4 NVMe PCIe drives or a mixture of SAS/SATA and NVMe drives. NVMe is an interface with lower overhead, lower latency and drastically increased bandwidth and IOP's. The RAID stack is based on the Broadcom MegaRAID® and offers high data throughput, a comprehensive fault tolerance function and user-friendly management

options. Moreover, the Controller management is integrated seamlessly into the Fujitsu server management concept. All controller functions are supported by the Fujitsu ServerView RAID Manager. The PRAID EP580i is designed for 3, 6 and 12Gbit/s SAS as well as for 3 and 6Gbit/s SATA drives. Regardless of the drive speed, it delivers significant performance improvements in both read and write applications. The controller firmware also supports FastPath® without an additional license. FastPath® accelerates the use of SSD only configurations. The RAID controller supports all of the important RAID levels including RAID 6 and 60. The optional flash battery backup (FBU) combined with the already included TFM module ensures the integrity of the data stored in the cache on the RAID controller in case of a power outage. In this event, the data will be copied to a non-volatile flash memory (TFM). The TFM module is bundled with the controller, the FBU is optional. Important information for later upgrade from or downgrade to std. SAS controller: Specific cable sets per system can be required as L-Part, please refer to Paper Configurator, order tool or controller and system documentation. Orders ex factory are configured with appropriate cables.



| Main Features | Benefits |
|--|--|
| Number of supported drives <ul style="list-style-type: none">■ 16 lines of 12Gbit/s SAS ports PCI Express® 3.0 RAID levels <ul style="list-style-type: none">■ SAS3516 12Gbit/s RAID-on-Chip | <ul style="list-style-type: none">■ Connect up to 64 HDDs and SSDs■ RAID levels 0, 1, 5 and 6 for more data security, RAID spans 10, 50 and 60 for more data security |
| Scalable performance <ul style="list-style-type: none">■ 16 lines of 8 Gbit/s PCIe Gen 3 for up to 4x x4 NVMe drives; 8GB 2133MHz DDR4 cache memory | <ul style="list-style-type: none">■ Improves performance for storage intensive workloads (such as databases) and for certain load profiles like random access to databases (especially for SSD drives) |
| Simplified management <ul style="list-style-type: none">■ User-friendly management options | <ul style="list-style-type: none">■ Seamless integration of RAID management |

Technical details

Technical details

| | |
|----------------------------------|---|
| Controller Silicon | RoC (RAID on Chip) SAS3516 |
| Adapter Type | RAID 5/6 Ctrl. |
| Operating system pre-installed | Information to released operating systems can be found in the server datasheets. Details can be found in the released drivers list on the support portal. |
| Released drivers list link | http://support.ts.fujitsu.com/Download/Index.asp |
| Number of ports | 16 ports int. |
| Connector internal | 4x SFF8643 (Mini-SAS HD) |
| Number of Connectors | 4 |
| Number of internal ports | 16 |
| Data transfer rate up to | 12 Gbit/s; 8 Gbit/s |
| Bus type | PCIe 3.0 |
| Bus width | x8 |
| RAID Management | ServerView RAID Manager StorCLI (command-line interface) BIOS Configuration Utility |
| Key RAID Data Protection Feature | <ul style="list-style-type: none"> - RAID levels 0, 1, 5 and 6 - RAID spans 10, 50 and 60 - Maximum number of spans is 8 - Online Capacity Expansion (OCE) - Online RAID level Migration (RLM) - Auto resume after loss of system power during array rebuild or reconstruction (RLM) - Fast initialization for quick array setup - Load Balancing - Configurable stripe size up to 1MB - Fast initialisation for quick array setup - Check consistency for background data integrity - Make Data Consistent (MDC) - Patrol read for media scanning and repairing - Up to 64 logical drives per controller - S.M.A.R.T support - Global and dedicated Hot Spare with Revertible Hot Spare support <ul style="list-style-type: none"> - Automatic rebuild - Enclosure affinity - Enclosure management <ul style="list-style-type: none"> - SES (inband) - SGPIO (outband) |
| RAID level | 0, 1, 10, 5, 50, 6, 60 |
| RAID cache backup unit | Optional FBU |
| RAID controller notes | based on SAS3516 |
| Interface technology | SAS/SATA/PCIe-NVMe |

| Order code | Product Name | Height of bracket | RAID controller cache size | Number of Connectors |
|-------------------|--------------------|---------------------------|----------------------------|----------------------|
| S26361-F4042-E208 | PRAID EP580i LP | Low Profile (LP) | 8 GB | 4 |
| S26361-F4042-E8 | PRAID EP580i FH | Full Height (FH) | 8 GB | 4 |
| S26361-F4042-L508 | PRAID EP580i FH/LP | Full Height / Low Profile | 8 GB | 4 |

| Order code | Product Name | Notes |
|-------------------|--|---|
| S26361-F4042-E155 | RAID Ctrl FBU option for PRAID EP5xx with 55cm cable | installed - Super-capacitor incl. cable |
| S26361-F4042-E183 | RAID Ctrl FBU option for PRAID EP5xx with 83cm cable | installed - Super-capacitor incl. cable |
| S26361-F4042-E171 | RAID Ctrl FBU option for PRAID EP5xx with 70cm cable for RX4770 M4 | installed - Super-capacitor incl. cable |
| S26361-F4042-L110 | RAID Ctrl FBU option for PRAID EP5xx with 25,55,83cm cable | installed - Super-capacitor incl. cable |
| S26361-F4042-L113 | RAID Ctrl FBU option for PRAID EP5xx with 70cm cable for RX4770 | installed - Super-capacitor incl. cable |

| | |
|------------------|---|
| Compliance | |
| Compliance notes | According to the corresponding system |
| Compliance link | https://sp.ts.fujitsu.com/sites/certificates |

More information

Fujitsu products, solutions & services

In addition to Fujitsu with PRAID EP580i, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio
Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products
www.fujitsu.com/global/products/computing/

Software
www.fujitsu.com/software/

More information

Learn more about Fujitsu PRAID EP580i, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
<http://www.fujitsu.com/primergy>

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2018 FUJITSU LIMITED

Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering. The product was developed for normal business use. Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.