Data Sheet
Fujitsu Display P34-9 UE

Ultrawide Curved 34.14 inch (86.72 cm) high performance Display
One that fits for all - our new wave of innovation!

The ultrawide FUJITSU Display P34-9 UE comes with a brilliant 3440x1440 resolution and a 1900R curvature. With the wide viewing angle and its almost bezelfree housing, it meets the requirements of various usage scenarios





Our curved 34.14-inch display with 21:9 aspect ratio at UWQHD resolution provides consistent clarity and a superior viewing experience.

The KVM function for common use of peripheral hardware for new connected USB-C devices makes it ideal for Shared Desk. The integrated built-in port replicator enables power delivery with only one USB Type-C cable to reduce the cable clutter for a clean desk approach.

Experience outstanding security due to our unique FUJITSU Presence Sensor with active PC-lock function, which meets even high data protection requirements in certain business segments.

The next generation IPS reduces response time as low as 2ms and advanced colors space match 98% DCI-P3, that provides perfect media consumption as creation. Combined with AMD FreeSync™ support, it's perfect to enjoy videos and gaming on highest level.

All in One: Videos out of two sources can be shown simultaneously by using the PIP (picture-in-picture) or PBP (picture-by-picture) function.

DisplayView™ software enables an easy monitor configuration for adjusting screen brightness, screen splitting and much more - best conditions for an optimized workspace with increased productivity.

Focusing on environmental friendliness, the packaging is styrofoam free and solely consisting of cardboard, which is more than 90% recycled.

Ongoing product improvement: the one-click firmware upgrade, made by the end user, opens the chance to get more and better features for already installed displays.

Technical details

Special features	
	Presence sensor with PC security solution In-Plane Switching (IPS) technology Color accuracy average DeltaE<2 Auto Brightness Control (ABC) Workplace Lighting Guide DisplayView™ Software Eco button for Eco mode and 4-colored status LED Cable guide Always available USB (in operating and standby mode) 24/7 usage Integrated speakers 5-in-1 Stand Smart Power ON and LED function for AiO-type usage (in combination with a dedicated FUJITSU systems e.g. ESPRIMO G or selected LIFEBOOK models)
Ergonomic stand	
Stand	5-in-1 Stand
Height adjust range	150 mm
Picture height over desk (min)	44 mm
Tilt angle	-5° ... 35° +/- 2.0°
Swivel angle	345°
Picture performance	
Panel and backlit	In-Plane Switching (IPS) technology/LED
Screen Surface Treatment	Anti-glare, 3H hard coating
Contrast - typical	1,000:1
Contrast - advanced	20,000,000:1
Response time gray to gray typical	2 ms (in Video mode)
Viewing angle (h/v) - typical	178°/178° CR10:1
Color performance	1.07 billion (8bit + A-FRC)
High color gamut - typical	98% DCI P3 color space
Brightness - typical	400 cd/m²
Size and resolution	
Aspect ratio	21:9
Diagonal Size	86.72 cm (34.14 inch)
Curvature	R1,900
Resolution (native)	3,440 x 1,440 pixel
Resolution (interpolated)	2,560 x 1,440 pixel, 2,560 x 1,080 pixel, 1,920 x 1,200 pixel, 1,920 x 1,080 pixel, 1,680 x 1,050 pixel, 1,600 x 900 pixel, 1,440 x 900 pixel, 1,280 x 1,024 pixel, 1,280 x 720 pixel, 1,024 x 768 pixel, 800 x 600 pixel, 640 x 480 pixel
Picture size	800 x 335 mm
Pixel Pitch	0.2325 mm
Frequencies	
Horizontal	30 - 160 kHz
Vertical	28 - 102 Hz
Connectivity	
DisplayPort	1 x DisplayPort Out (Daisy Chain), 1 x DisplayPort 1.2
HDMI	2 x HDMI 2.0
Audio signal output	3.5 mm stereo phone jack for head phone
Audio sound output	2 x 3 W
DisplayPort audio	Yes
HDMI audio	Yes
USB downstream	4 x USB 3.2 gen 1 (2 side USB: 1x Type A + 1x Type-C ; 2 bottom USB: Type-A)

USB upstream	1 x USB-C with alternate mode for video data and power delivery up to 65W (USB 2.0 performance in combination with DaisyChain) 1 x USB 3.2 gen 1 (5 Gbps) Type B Integrated KVM switch function
Ethernet (RJ-45)	1 x Gigabit LAN (300Mbps in combination with DaisyChain) PXE, Wake on LAN, MAC Address Pass Through support with selected LIFEBOOK models
Ease-of-use menu	
Notes	6 tactile keys on front side
Direct Access Keys	Menu, ECO, Input, Mode, Audio, Brightness
Languages	Arabic, Czech, Danish, Dutch, English, Finnish, French, German, Italian, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Japanese, Chinese simply, Chinese traditional
Brightness / Contrast	Brightness, Contrast, Black level, Auto Brightness, ACR, Lighting Guide
Mode	sRGB, Office, Photo, Video, Low Blue Light, Custom
Color	5000K, 6500K, 7500K, Native, RGB Adjust
OSD	Language, OSD-Timeout, OSD rotation
Image adjust	Sharpness, Saturation, Hue, Expansion
Audio	Mute, Volume, Input for HDMI and DP interface
Information	Model name, Serial number, Signal input, Resolution/mode, Display mode , Color Temperature, ACR Status, ABC Status
Picture in Picture (PIP)	Input, Mode, Position, USB Upstream, Swap
Advanced settings	Presence Sensor, Proximity Adjust, Daisy Chain, FreeSync, Overdrive, DDC/CI, Status LED, Power Button, Factory Recall
Power consumption (typical)	
Soft switch off	0.24 W
Power save mode	0.26 W
Operating with EPA settings	33.34 W
Total Energy Consumption (ETEC)	105.52 kWh/year
Operating maximum brightness	51 W
Power supply	integrated
Power notes	Speakers off, USB not connected ETEC and EPA refer to ENERGY STAR® 8.0 Power save mode according to EEI test conditions
Electrical values	
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Protection class	1
Compliance	
Model	P34-9U
Global	ENERGY STAR® 8.0, Zero bright and dark pixel faults, Subpixel faults according to ISO9241-307 (Pixel fault class I), TÜV Flicker Free Certified, TÜV Low Blue Light Certified, IEC 62368-1, EPEAT® Silver (dedicated regions), TCO Certified, generation 9
Europe	EN 62368-1, CE certification according to EC Directive 2004/108/EEC, RoHS, WEEE, IT-Eco-Declaration
Australia/New Zealand	(on customer request)
Germany	TÜV GS
Singapore	S-Mark
South Korea	KC, E-Standby
Taiwan	BSMI
USA/Canada	FCC Class B, cTUVus
Compliance link	https://sp.ts.fujitsu.com/sites/certificates
Dimensions / Weight / Environmental	
Dimension without stand (W x D x H)	814.82 x 109.39 x 372.8 mm
	32.08 x 4.31 x 14.68 inch
Dimension with stand (W x D x H)	814.82 x 275 x 390.3 mm
	32.08 x 10.83 x 15.37 inch

Weight (unpacked)	8.8 kg
	19.40 lbs
Weight (Monitor only)	6.23 kg
	13.73 lbs
Operating ambient temperature	5 - 35 °C
Operating relative humidity	15 - 85% (non condensing)
Miscellaneous	
Miscellaneous	VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared
Color	Marble grey
Additional Software	
Additional software (optional)	WINDOWS WHQL driver Realtek USB Ethernet Controller driver DisplayView Suite DisplayUpdate Power Delivery Update
Additional software (notes)	Use of accompanying and/or additional Software is subject to proactive acceptance of the respective License Agreements /EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration.
Package content	
Display delivered accessories	DisplayPort data cable 1.8 m HDMI cable 1.8 m USB cable 1m (USB-C to USB-C) USB-cable 1.8 m (USB-A to USB-B) Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m Quickstart flyer Safety notes
Display delivered accessories notes	Power cable with IEC-60320-C13, 3-pin connector on display side Data cables and USB cable detachable on display User manual and DisplayView Software is available via download DisplayView Software is necessary for Presence Sensor PC security solution
Packaging information	
Packaging dimension (mm)	965 x 482 x 285 mm
Packaging dimension (inch)	37.99 x 18.98 x 11.22 inch
Weight (packed)	13.8 kg
Weight (packed) (lbs)	30.42 lbs
Order information	
Order Code	S26361-K1710-V140
EAN Code	4065221888246
Country specific order code	BDL:K1710V140-UK - with UK power cable, mandatory for Arabian countrie
Accessories information	Further helpful options: Stands and Mounting kits: http://www.fujitsu.com/fts/products/computing/peripheral/accessories/desktop/ums/index.html Available Adapters: http://globalsp.ts.fujitsu.com/dmsp/Publications/public/pos-connectivity.pdf
Warranty	
Warranty period	3 years (depending on country)
Warranty Terms & Conditions	http://www.fujitsu.com/warranty
Digital bug fixes	Subject to availability and following their generic release for the product, bug fixes and function-preserving patches for product-related software (firmware) can be downloaded from the technical support at: https://support.ts.fujitsu.com/ free of charge by entering the respective product serial number. For application software supplied together with the product, please directly refer to the support websites of the respective software manufacturer.
Spare Parts availability	at least 7 years after shipment, for details see https://support.ts.fujitsu.com/
Service Weblink	http://www.fujitsu.com/emeia/products/product-support-services/

More information

Fujitsu products, solutions & services

In addition to Fujitsu Display P34-9 UE, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio
Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products
www.fujitsu.com/global/products/computing/

Software
www.fujitsu.com/software/

More information

Learn more about Fujitsu Display P34-9 UE, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/emeia/products/computing/peripheral/displays

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.
Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.
Please find further information at http://www.fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see https://www.fujitsu.com/global/about/resources/terms/
Copyright 2024 Fujitsu Technology Solutions GmbH

Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering.
Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.
The overall product has been designed and manufactured for general office use, regular personal use and ordinary industrial use.

CONTACT
Fujitsu Technology Solutions GmbH
Website: www.fujitsu.com
2024-03-06 EM-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see https://www.fujitsu.com/global/about/resources/terms/
Copyright 2024 Fujitsu Technology Solutions GmbH